





Fuse Links for battery powered industrial trucks. 80 V DIN 43560/1

Open Fuse Links Form A,



Rating A	Art.-Nr.	kg/100
50	90 030 05	0,5
63		
80		
100		
125		
160		
200		
250		
300		
355		
425		

Enclosed Fuse Links Form B,




Rating A	Art.-Nr.	kg/100
50	90 058 05	1,9
63		
80		
100		
125		
160		
200		
250		
300		
355		
425		

Test Specifications

Load	Opening Time
150 %	> 1 Std., 1 Hour
180 %	< 1 Std., 1 Hour
250 %	0,8 - 10 Sec.
400 %	0,2 - 2 Sec.

Open Fuse of various dimensions



Contact pieces and fusing-elements in one piece.

Fixing centres mm	Slots mm	Rating A	Art.-Nr.	kg/100
70	7	35	90 051 02	0,2
		50		
		63		
80	9	35	90 052 02	0,4
		50		
		63		
		80		
95	11	100	90 038 02	0,6
		125		
		160		
		200		
		250		



When ordering to indicate: — Amp.
— mm / fixing centres
— mm / slots

Copper contact. Hard soldered fuse-wires. Surface nickel-plated.
Minimum order quantity 100 pcs. of each required Amp. rating and design.

Slots mm	Rating A	Art.-Nr.	kg/100
7	35	90 001 02	0,5
	50		
	63		
9	35	90 002 02	0,8
	50		
	63		
	80		
11	100	90 003 02	1,4
	125		
	160		
	200		
	250		
14	160	90 004 02	3,1
	200		
	224		
	250		
	300		
	355		
17	355	90 005 02	6,5
	425		
	500		
	630		

Test Specifications

Load	Opening Time
160 %	> 1 Std., 1 Hour
180 %	< 1 Std., 1 Hour



SICHERUNGEN-BAU GMBH

Borker Straße 22 · Postfach 1940 · D-4670 Lünen

Telefon (02306) 7001-0 · Teletex 2306300 SIBALUE · Telegramm: SIBA D 4670 Lünen

Medium Time current characteristic

