# **SPECIFICATION**

Product name Rodan Spark Gap

Type RSG-802-BQL



Version

First

OKAYA ELECTRIC AMERICA, INC.


Spec No.	SS-024
Data	Oct 30, 2003

**1. Scope** This specification covers Rodan Spark Gap RSG-802-BQL.

#### 2. Type designation

First

Version



## 3. Appearance Structure

- 3-1 Dimension Refer to drawing 4R-4198-Y89
- 3-2 Display and contents Marking must not be disappeared easily, and it has to be identified.




Fig.1 Example of marking

3-3 Materials Ceramic, Electrode, Lead wire etc

3-4 Plating treatment Tinning

3-5 Filler gas Ar, mixed gas This product doesn't use radioisotope.



## OKAYA ELECTRIC AMERICA, INC.

Spec No. SS-
Data Oct 30

## 4. Electrical characteristics

First

Version

No.	Item	Mark	Т	Standard values	
1	DC breakdown voltage	Ez	$1 \text{ M}\Omega$ , $500 \text{ V/s}$	8000 V ±20 %	
2	Insulation resistance	IR	DC100 V	1000 MΩ Min	
3	Electrostatic capacitance	С	1.0 kHz	2.0 pF Max	
4	Life test	1	Switching frequency	100 Hz	
			Switching times	5 s ON / 55 s OFF	DC breakdown
			Ambient temperature	Room temperature	Voltage
			Test circuit		8000 V <sup>+20</sup> <sub>-25</sub> %  Insulation resistance 100 MΩ Min (DC100 V)
			V <sub>0</sub> =12 kV C=2400 pF OSC		
			* R is adjusted		
			Minimum number of switching is 10 <sup>5</sup> times, according to the above condition.		



Spec No.	SS-024
Data	Oct 30, 2003
Version	First

## 5. Switching frequency

Maximum switching frequency: 200 Hz

## 6. Operating condition

Operating temperature : -40 to +100


## 7. Storage condition

Storage temperature : -40 to +100

## 8. About forming

As regards forming of spark gap, please take distance more than 2mm from main body when you bend lead wire.

When performing a forming, please hold only lead wire and be careful not to give a stress on main body.








Spec No.	SS-024
Data	Oct 30, 2003
Version	First

## 9. Packing

Put 50 pcs. of RSG series and 1pc. of product label in a vinyl bag of specified size, seal the bag with a heatseal, put bags of quantity required a box, pack and stick product label on the box.







# Weight:approx. 2.5 g

Ver.	Rev. da ta	History of rev.	Date		Sca le	Product name		
			2003 .10 .30		2:1	Rodan spark gap		)
						Type name Outline dimension		
						Dra	$\frac{8.0 \times 11.5}{4 \times 10^{-10}}$ No.	5 L)
	OKAYA ELECTRIC AMERICA, INC.					4R-4	1198 - Y89	4