


SBT1020 ... SBT10100

Schottky Barrier Rectifiers Schottky-Barrier-Gleichrichter

Version 2005-12-07



Dimensions - Maße [mm]

Nominal current Nennstrom	10 A
Repetitive peak reverse voltage Periodische Spitzensperrspannung	20...100 V
Plastic case Kunststoffgehäuse	TO-220AC
Weight approx. Gewicht ca.	1.8 g
Plastic material has UL classification 94V-0 Gehäusematerial UL94V-0 klassifiziert	
Standard packaging taped in tubes Standard Lieferform in Stangen	

Maximum ratings and Characteristics**Grenz- und Kennwerte**

Type Typ	Repetitive peak reverse voltage Periodische Spitzensperrspannung V_{RRM} [V]	Surge peak reverse voltage Stoßspitzensperrspannung V_{RSM} [V]	Forward voltage Durchlass-Spannung V_F [V] ¹⁾	
			$I_F = 5 \text{ A}$	$I_F = 10 \text{ A}$
SBT1020	20	20	< 0.47	< 0.54
SBT1030	30	30	< 0.47	< 0.54
SBT1040	40	40	< 0.47	< 0.54
SBT1045	45	45	< 0.47	< 0.54
SBT1050	50	50	< 0.57	< 0.64
SBT1060	60	60	< 0.57	< 0.64
SBT1090	90	90	< 0.72	< 0.79
SBT10100	100	100	< 0.72	< 0.79

Max. average forward rectified current, R-load
Dauergrenzstrom in Einwegschaltung mit R-Last

$T_c = 100^\circ\text{C}$ I_{FAV} 10 A

Repetitive peak forward current
Periodischer Spitzenstrom

$f > 15 \text{ Hz}$ I_{FRM} 30 A²⁾

Peak forward surge current, 50/60 Hz half sine-wave
Stoßstrom für eine 50/60 Hz Sinus-Halbwelle

SBT1020... SBT1060 $T_A = 25^\circ\text{C}$ I_{FSM} 135/150 A

Peak forward surge current, 50/60 Hz half sine-wave
Stoßstrom für eine 50/60 Hz Sinus-Halbwelle

SBT1090... SBT10100 $T_A = 25^\circ\text{C}$ I_{FSM} 115/125 A

Rating for fusing, $t < 10 \text{ ms}$
Grenzlastintegral, $t < 10 \text{ ms}$

$T_A = 25^\circ\text{C}$ I^2t 80 A²s

Junction temperature – Sperrschiichttemperatur
Storage temperature – Lagerungstemperatur

T_j -50...+150°C
 T_s -50...+175°C

1 $T_j = 25^\circ\text{C}$

2 Max. temperature of the case $T_c = 100^\circ\text{C}$ – Max. Temperatur des Gehäuses $T_c = 100^\circ\text{C}$

Characteristics
Kennwerte

Leakage current Sperrstrom	SBT1020 ... SBT1040	$T_j = 25^\circ\text{C}$ $T_j = 100^\circ\text{C}$	$V_R = V_{RRM}$ $V_R = V_{RRM}$	I_R I_R	< 500 μA < 45 mA
Leakage current Sperrstrom	SBT1045 ... SBT10100	$T_j = 25^\circ\text{C}$ $T_j = 100^\circ\text{C}$	$V_R = V_{RRM}$ $V_R = V_{RRM}$	I_R I_R	< 300 μA < 25 mA
Thermal resistance junction to case Wärmewiderstand Sperrsicht – Gehäuse				R_{thC}	< 3 K/W

