


DB ELECTRO ^{UN}

Présente / Presents:

NINGBO HUAGUAN ELECTRONICS CO.,LTD.





23.1 × 17.2 × 16.2



NSAM

Features

- Switching capacity up to 20A.
- PC board mounting.
- Suitable for automobile accessories.

Ordering Information

NSAM 2C S 15 12VDC
 1 2 3 4 5

1 Part number: NSAM

2 Contact arrangement: 2A:2A; 2C:2C;

3 Enclosure: S: Sealed type; Z: Dust cover

4 Contact current: 7A,10A,15A,20A

5 Coil rated voltage(V): DC:5,6,9,12,18,24

Contact Data

Contact Arrangement	2A (DPSTNO) ,2C (DPDT(B-M))		
Contact Material	AgSnO ₂		
Contact Rating (resistive)	NO: 15A,20A/15VDC, 10A,15A/24VDC,125VAC ; NC: 10A,15A/15VDC,125VAC; 7A,10A/24VDC		
Max. Switching Power	300W 2000VA		
Max. Switching Voltage	30VDC 220VAC	Max. Switching Current:20A	
Contact Resistance or Voltage drop	≤50mΩ		Item 3.12 of IEC255-7
Operation life	Electrical	10 ⁵	Item 3.30 of IEC255-7
	Mechanical	10 ⁷	Item 3.31 of IEC255-7

Coil Parameter

Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pickup voltage VDC(max) (75%of rated voltage)	Release voltage VDC(min) (5% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
	Rated	Max.						
005-450	5	6.5	56	3.75	0.25	0.45	≤10	≤5
006-450	6	7.8	80	4.50	0.30			
009-450	9	11.7	180	6.75	0.45			
012-450	12	15.6	320	9.00	0.60			
018-450	18	23.4	720	13.5	0.90			
024-450	24	31.2	1280	18.0	1.20			

- CAUTION:** 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.