



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 1191.795 MHz SMD 3.0x3.0 mm

TST Part No.: TA1170A

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ David Chang 張閔智

Approved by: _____ Francis Chen 陳國良

Date: _____ 2010/02/09

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com

Web: www.taisaw.com

SAW Filter 1191.795 MHz

MODEL NO.:TA1170A

REV. NO.:2

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3 V
3. Operating Temperature: -20°C to +70°C
4. Storage Temperature: -40°C to +85°C


RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Type.	Max.
Center frequency F_c	MHz	-	1191.795	-
Insertion Loss (1175.795~1207.795 MHz) IL	dB	-	2.4	3.5
Amplitude Ripple (1175.795~1207.795 MHz)	dB	-	0.7	2.0
VSWR (1175.795~1207.795 MHz)	-	-	2.1	2.4
Attenuation (Reference level from 0 dB)				
0.3 ~ 300 MHz	dB	30	36	-
300 ~ 1110 MHz	dB	24	30	-
1110 ~ 1145 MHz	dB	30	34	-
1250 ~ 1290 MHz	dB	30	37	-
1290 ~ 1780 MHz	dB	27	32	-
1780 ~ 2000 MHz	dB	30	34	-

C. MEASUREMENT CIRCUIT:

HP Network analyzer




D.OUTLINE DRAWING:





△ : Year Code (2006->6, ..., 2009->9)

□ : Date Code (W01->A,W02->B,...W27->a,...,W52->z)

E. PCB Footprint:




F. Frequency Characteristics:




G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

