

2SC3085

2017

NPN Triple Diffused Planar
Silicon Transistor

T-33-15

Switching Regulator Applications

©1055A

Features

- High breakdown voltage ($V_{CB0} \geq 500V$)
- Fast switching speed.
- Wide ASO.

Absolute Maximum Ratings at $T_a = 25^\circ C$

			unit
Collector to Base Voltage	V_{CB0}	500	V
Collector to Emitter Voltage	V_{CE0}	400	V
Emitter to Base Current	I_{EB0}	7	A
Collector Current	I_C	25	A
Peak Collector Current	i_{cp}	40	A
	$PW \leq 300\mu s$, Duty Cycle $\leq 10\%$		
Base Current	I_B	8	A
Collector Dissipation	P_C	160	W
Junction Temperature	T_J	150	$^\circ C$
Storage Temperature	T_{stg}	-55 to +150	$^\circ C$
	$T_c = 25^\circ C$		


Electrical Characteristics at $T_a = 25^\circ C$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = 400V, I_E = 0$			10	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 5V, I_C = 0$			10	μA
DC Current Gain	$h_{FE}(1)$	$V_{CE} = 5V, I_C = 3.2A$	15*		50*	
	$h_{FE}(2)$	$V_{CE} = 5V, I_C = 16A$	8			
Gain Bandwidth Product	f_T	$V_{CE} = 10V, I_C = 3.2A$		20		MHz
Output Capacitance	c_{ob}	$V_{CB} = 10V, f = 1MHz$		320		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = 16A, I_B = 3.2A$		1.0		V
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = 16A, I_B = 3.2A$		1.5		V
C-B Breakdown Voltage	$V_{(BR)CB0}$	$I_C = 1mA, I_E = 0$	500			V
C-E Breakdown Voltage	$V_{(BR)CE0}$	$I_C = 10mA, R_{BE} = \infty$	400			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 1mA, I_C = 0$	7			V
C-E Sustain Voltage	$V_{CEO(sus)}$	$I_C = 25A, L = 50\mu H, I_B = 5A$	400			V
C-E Sustain Voltage	$V_{CEX(sus)}$	$I_C = 25A, I_{B1} = 5A, L = 200\mu H$	400			V
	(1)	$I_{B2} = -5A, \text{clamped}$				
C-E Sustain Voltage	$V_{CEX(sus)}$	$I_C = 6A, I_{B1} = 1.2A, L = 200\mu H$	450			V
	(2)	$I_{B2} = -1.2A, \text{clamped}$				

*: The $h_{FE}(1)$ of the 2SC3085 is classified by 3.2A h_{FE} as follows. When specifying the $h_{FE}(1)$ rank, specify two ranks or more in principle.

15	L	30	20	M	40	30	N	50
----	---	----	----	---	----	----	---	----

Case Outline 2017 (unit:mm)



ETAJ. TC-3, TB-3
JEDEC. TO-3

C:Collector
E:Emitter
B:Base








4207KI/2125MW, TS No.1055-1/3

2SC3085

T-33-15





			min	typ	max	unit
Turn-ON Time	t_{on}	$I_C=20A, I_{B1}=4A, I_{B2}=-4A,$ $R_L=10\Omega, V_{CC}=200V$			1.0	us
Storage Time	t_{stg}				2.5	us
Fall Time	t_f				1.0	us

Switching Time Test Circuit



2SC3085

T-33-15




T-91-20

CASE OUTLINES AND ATTACHMENTS

- All of Sanyo Transistor case outlines are illustrated below.
- All dimensions are in mm, and dimensions which are not followed by min. or max. are represented by typical values.
- No marking is indicated.


Case Outline—[2003A]

unit:mm




Case Outline—[2009A]

unit:mm




Case Outline—[2004A]

unit:mm




Case Outline—[2010A]

unit:mm




Case Outline—[2005A]

unit:mm




Case Outline—[2012]

unit:mm




Case Outline—[2006A]

unit:mm




Case Outline—[2013]


unit:mm



unit:mm




unit:mm




T-91-20


unit:mm




unit:mm




unit:mm




unit:mm




unit:mm




unit:mm



unit:mm



unit:mm



E: Emitter
C: Collector
B: Base

SANYO:DP6B

E: Emitter
C: Collector
B: Base

G1: Catw1
\$: Source
D-r Drain
G2: Gate2
SANYO: OP4A

E: Emitter
C: Collector
B: Base

SANYO:TO3PML

B: Base
C: Collector
E: Emitter
SANYO: SPA

G: Gate
S: Source
D: Drain
SANYO: SPA

D: Drain
G: Gate
S: Source
SANYO: SPA


SANYO: TO220ML

D: Drain
G: Gate
S: Source
SANYO: SP'

SANYO: TO126ML

T-91-20

unit:mm




SANYO: TO126LP

G : Gate
S : Source
D : Drain


SANYO : CP

unit:mm




C : Collector
E : Emitter
B : Base
SANYO: SPA

unit:mm



JEDEC: TO-220AB
EIAJ: SC-46


unit:mm



SANYO : TO- 3PBL

1: Drain
2: Source
3: Gate 1
4: Gate 2

unit:mm




SANYO:TO-220MF

E: Emitter
C: Collector
B: Base


SANYO: CP

Case Outline—[2056] unit:mm



SANYO: TO3PB


Case Outline—[0008] unit:mm

a. IS-313B
b. IS-313D

SANYO

Case Outline—[0004] unit:mm

unit:mm




SANYO IS-126

Thickness : 0.075

Case Outline—[0009] unit:mm

unit:mm




SANYO Bush

Bush	D	H	h ₁	h ₂	h ₃
A	8.0φ	4.0	2.8	3.1φ	3.89φ
B	8.0φ	3.0	1.8	3.1φ	3.89φ
C	8.0φ	5.7	4.5	3.1φ	3.89φ
D	8.0φ	2.7	1.5	3.1φ	3.89φ
E	8.0φ	3.4	2.2	3.1φ	3.89φ
F	8.0φ	4.0	2.8	3.0φ	3.59φ
K	16.0φ	3.4	1.4	3.1φ	6.0φ
L	6.0φ	3.1	1.5	2.6φ	3.5φ
M	6.0φ	3.1	1.5	3.0φ	3.59φ
P	6.0φ	2.3	1.1	3.0φ	3.59φ

Case Outline—[0005] unit:mm

unit:mm




Thickness : 0.075

SANYO IS-126A Mica

Case Outline—[0010] unit:mm

unit:mm




SANYO Bush

Bush	D	H	h ₁	h ₂	h ₃	h ₄	h ₅
H	9.0φ	4.0	2.0	0.8	3.0φ	3.59φ	5.6φ
T	9.0φ	5.8	2.0	2.6	3.0φ	3.59φ	5.6φ
UB	16.0φ	6.8	1.5	3.3	3.0φ	3.89φ	8.0φ

Case Outline—[0006] unit:mm

unit:mm




Thickness : 0.05~0.1

SANYO IS-20MA Mica

Case Outline—[0011] unit:mm


unit:mm



JIS No. B1111 M3×0.5


Case Outline—[0007] unit:mm

unit:mm



Case Outline—[0012] unit:mm


unit:mm



JIS No. B1111 M3×0.5

Case Outline—[0013]


unit:mm



JIS No. B1111 M3×0.5

Case Outline—[0018]

unit:mm




SANYO Lug 1.4

T=91-20

Case Outline—[0014]


unit:mm



JIS No. B1181 M3×0.5

Case Outline—[0019]


unit:mm



SANYO Lug 1.8φ

Case Outline—[0015]


unit:mm



JIS No. B 1251 Spring washer (M3)

Case Outline—[0020]


unit:mm



SANYO IS-3MP Mica

Case Outline—[0016]


unit:mm



JIS No. B1252 Flat washer

Case Outline—[0021]


unit:mm



SANYO IS-MPC Mica

Case Outline—[0017]


unit:mm



JIS No. G3141 Rectangular washer

Case Outline—[0022]

unit:mm



SANYO IS-3PBL Mica