

E-Series 2-Way 90° Power Divider

40 - 70 MHz

ESQ-2-70

V3.00

Features

- 2 Way
- 90°

Specifications @ 25°C

Frequency Range		40 - 70 MHz
Insertion Loss	Typical	Maximum
40 - 70 MHz	0.3 dB	0.7 dB
Isolation	Typical	Minimum
40 - 70 MHz	30 dB	20 dB
Amplitude Unbalance		Maximum
40 - 70 MHz		1.5 dB
Phase Unbalance		Maximum
40 - 70 MHz		3°

Operating Characteristics

Impedance	50 Ohms Nominal
-----------	-----------------

Ordering Information


Part No.
ESQ-2-70

Packaging
Tube

Absolute Maximum Ratings

Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 sec)	260°C
Storage Temperature	-55°C to 100°C

R-2



Dimensions in () are in mm.

Unless Otherwise Noted: .x = ±0.04 (1.00)

.xx = ±0.02 (0.50)

.xxx = ±0.010 (0.250)

WEIGHT (APPROX.): 0.23 OUNCES 6.3 GRAMS

Pin Configuration

Function	Pin No.
Not Connected	3,4,7,8
External 50 Ohms	6
Input	1
Port 1	2
Port 2	5

S 0213 B