

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with
2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN
devices".

<u>5962-86708</u>	<u>01</u>	<u>E</u>	<u>X</u>
Drawing number	Device type (1.2.1)	Case outline (1.2.2)	Lead finish per MIL-M-38510

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	25LS09 or 25LS399	Quad two-input, high speed register

<u>Outline letter</u>	<u>Case outline</u>
E	D-2 (16-lead, 1/4" x 7/8"), dual-in-line package
F	F-5 (16-lead, 1/4" x 3/8"), flat package

Supply voltage range	-0.5 V dc to +7.0 V dc
Input voltage range	-1.5 V dc to +7.0 V dc
Storage temperature range	-65°C to +150°C
Maximum power dissipation (P _D) 1/	600 mW
Lead temperature (soldering, 10 seconds)	+300°C
Thermal resistance, junction-to-case (θ _{JC}):	
Case E	30°C/W
Case F	25°C/W
Junction temperature (T _J)	+150°C
DC output current into outputs	30 mA
DC input current	-30 mA to +5.0 mA

Supply voltage (V_{CC})	- - - - -	+4.5 V dc minimum to +5.5 V dc maximum
Minimum high-level input voltage (V_{IH})	- - - -	2.0 V dc
Maximum low-level input voltage (V_{IL})	- - - -	0.7 V dc
Ambient temperature range (T_A)	- - - - -	-55°C to +125°C

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 2

Powered by ICminer.com Electronic-Library Service Copyright 2003

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Truth table. The truth table shall be as specified on figure 2.

3.2.3 Logic diagram. The logic diagram shall be as specified on figure 3.

3.2.4 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full recommended ambient operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 3

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
High level output voltage	V _{OH}	V _{CC} = 4.5 V, I _{OH} = -440 μA V _{IN} = 0.7 V or 2.0 V	1, 2, 3	2.5		V
Low level output voltage	V _{OL}	V _{CC} = 4.5 V V _{IN} = 0.7 V or 2.0 V	I _{OL} = 4.0 mA 1, 2, 3		0.4	V
			I _{OL} = 8.0 mA 1, 2, 3		0.45	V
Input clamp voltage	V _{IC}	V _{CC} = 4.5 V, I _{IN} = -18 mA	1, 2, 3		-1.5	V
Low level input current	I _{IL}	V _{CC} = 5.5 V V _{IN} = 0.4 V	Clock, S 1, 2, 3		-0.36	mA
			Others 1, 2, 3		-0.24	mA
High level input current	I _{IH1}	V _{CC} = 5.5 V V _{IN} = 2.7 V	Clock, S 1, 2, 3		20	μA
			Others 1, 2, 3		14	μA
	I _{IH2}	V _{CC} = 5.5 V, V _{IN} = 7.0 V	1, 2, 3		100	μA
Output short circuit current	I _{OS}	V _{CC} = 5.5 V, V _{OUT} = 0.0 V <u>1/</u>	1, 2, 3	-15	-85	mA
Power supply current	I _{CC}	V _{CC} = 5.5 V Select = Clock = 4.5 V <u>2/</u>	1, 2, 3		18	mA
Propagation delay time, clock to Q high	t _{PLH}	V _{CC} = 4.5 V to 5.5 V C _L = 50 pF R _L = 2.0 k	9,10,11		35	ns
		V _{CC} = 5.0 V C _L = 15 pF R _L = 2.0 k T _A = +25°C	9		20	ns
	t _{PHL}	V _{CC} = 4.5 V to 5.5 V C _L = 50 pF R _L = 2.0 k	9,10,11		35	ns
		V _{CC} = 5.0 V C _L = 15 pF R _L = 2.0 k T _A = +25°C	9		20	ns

See footnotes at end of table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 4

DESC FORM 193A
FEB 86

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
Clock pulse width	t _{pw}		9, 10, 11	30		ns
		T _A = +25°C	9	17		ns
Data setup time	t _s		9, 10, 11	35		ns
		T _A = +25°C	9	20		ns
Select input setup time	t _s		9, 10, 11	50		ns
		T _A = +25°C	9	30		ns
Data hold time	t _h		9, 10, 11	12		ns
		T _A = +25°C	9	5		ns
Select input hold time	t _h		9, 10, 11	5		ns
		T _A = +25°C	9	0		ns

1/ Not more than one output should be shorted at a time, and the duration of the short circuit condition should not exceed one second.

2/ Measured with select and clock inputs at 4.5 V; all data inputs at 0 V; all outputs open.

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 5

DESC FORM 193A
FEB 86

Cases E and F




FIGURE 1. Terminal connections.

SELECT S	CLOCK CP	DATA D _{iA}	INPUTS D _{iB}	OUTPUT Q _i
L	↑	L	X	L
L	↑	H	X	H
H	↑	X	L	L
H	↑	X	H	H

H = HIGH Voltage Level
 X = Don't Care
 ↑ = LOW-to-HIGH Transition

L = LOW Voltage Level
 i = 0, 1, 2, or 3

FIGURE 2. Truth table.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 6

DESC FORM 193A
 FEB 86




FIGURE 3. Logic diagram.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 7

DESC FORM 193A
FEB 86

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

- a. Burn-in test (method 1015 of MIL-STD-883).
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 4, 5, 6, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.
- c. Subgroup 7 tests shall verify the truth table.

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*, 2, 3, 7, 8, 9
Group A test requirements (method 5005)	1, 2, 3, 7, 8, 9, 10**, 11**
Groups C and D end-point electrical parameters (method 5005)	1, 2, 3

* PDA applies to subgroup 1.

** Subgroups 10 and 11, if not tested, shall be guaranteed to the specified limits in table I.

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 8

DESC FORM 193A
FEB 86

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test (method 1005 of MIL-STD-883) conditions:
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by appendix B of MIL-M-38510 and method 1005 of MIL-STD-883.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

6.4 Approved source of supply. An approved source of supply is listed herein. Additional sources will be added as they become available. The vendor listed herein has agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number ^{1/}
5962-8670801EX	34335	AM25LS09/BEA or AM25LS399/BEA
5962-8670801FX	34335	AM25LS09/BFA or AM25LS399/BFA

^{1/} Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

34335

Vendor name
and address

Advanced Micro Devices, Inc.
901 Thompson Place
P. O. Box 3453
Sunnyvale, CA 94088

MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO	SIZE A	CODE IDENT. NO. 14933	DWG NO. 5962-86708
		REV	PAGE 9

DESC FORM 193A
FEB 86