

NOTE 1. PRODUCTION LOT No. AS INDICATED.
(Ex.) T501

LOT NUMBER OF CURRENT MONTH

MONTH (1 TO 9 FOR JAN. TO SEPT. RESPECTIVELY,
OCT.:0, NOV.:X, DEC.:Y)

[illegible]

MANUFACTURE CODE

NOTE 2. CARD THICKNESS APPLIES ACROSS TABS AND INCLUDES PLATING AND/OR METALIZATION.

NOTE 3. BEVEL MUST BE FREE OF CUTTING BURRS.

NOTE 4. THE HORIZONTAL AXIS FOR THE PATTERN IS ESTABLISHED BY A LINE THROUGH THE CENTER OF THE $\phi 1.6$ AND $\phi 1.1$ HOLES.

THE VERTICAL AXIS IS 90° TO THE HORIZONTAL AXIS, THROUGH THE CENTER OF DATUM F.

NOTE 5. LOCATION OF INSERTED CARD EDGE IS ALIGNED WITH ϕ OF HOLES.

NOTE 6. ONLY WHEN THE LATCH SHOWN IN SJ105221(MM60-EZH059-B5) IS USED, THESE DIMENSIONS ARE APPLIED.

MM60-52B1-E*

SERIES PREFIX

No. OF CONTACTS

SOCKET TYPE


KEYING TYPE

CONTACT FINISH			
1:	Au(0.1 μ m Min.)	OVER	NI
2:	Au(0.3 μ m Min.)	OVER	NI

MODIFY CODE
E:5.9mm HIGHT WITH BOSS

HATCHED AREAS ILLUSTRATE MAXIMUM
AVAILABLE COMPONENT VOLUME.

APPLICABLE DIMM(REF.)

SIZE A2