


VTE-205H

Through hole VC-TCXO
HCMOS / TTL compatible



QuartzCom
the communications company



Features

- Applications: mobile communications, instrumentation
- Frequency range up to 200 MHz
- Tight frequency stability vs. temperature
- Low phase noise

Parameter	Specification	
	VTE-205H3	VTE-205H5
Frequency range	1 ~ 200 MHz	
Standard frequencies	8.192, 10.00, 12.80, 13.00, 16.384, 20.00, 25.00, 27.00 & 38.40 MHz	
Frequency stability:		
vs. temperature	$\leq \pm 0.5 \sim \pm 2.5$ ppm	
vs. supply & load change	$\leq \pm 0.2$ ppm	± 5 %
vs. aging	$\leq \pm 1.0$ ppm	1 st year
Frequency tolerance ex. factory	$\leq \pm 0.5$ ppm	@ +25 °C
Supply voltage	+3.3 V ± 5 %	+5.0 V ± 5 %
Supply current	10 ~ 40 mA	
Output signal	HCMOS / TTL compatible	
Output level	$V_{OH} > 0.9$ Vdc	$V_{OL} < 0.1$ Vdc
Output load	15 pF / 10 TTL	
Frequency pulling range	$\pm 10 \sim \pm 25$ ppm	
Voltage control	+1.65 V ± 1.50 V	+2.5 V ± 2.0 V
Frequency adjustment (optional)	$> \pm 5$ ppm	with internal trimmer
Operating temperature range	-30 ~ +75 °C -40 ~ +85 °C	commercial application industrial application
Storage temperature range	-55 ~ +125 °C	
Packaging unit	cardboard box	50 pieces
Customer specifications on request		



Pin function

- # 1 Vdc Supply voltage
- # 2 RF Output
- # 3 GND
- # 4 Vc Voltage control
- # 5 GND



Phase noise @ 20 MHz	-100 dBc/Hz	@	10 Hz
	-128 dBc/Hz	@	100 Hz
	-140 dBc/Hz	@	1 kHz
	-147 dBc/Hz	@	10 kHz
	-152 dBc/Hz	@	100 kHz

Environmental & Mechanical specification

Shock	MIL-STD-883C, Method 2002, Con B
Vibration	MIL-STD-883C, Method 2007, Con A
Solderability	MIL-STD-883C, Method 2003
Seal integrity	MIL-STD-883C, Method 2014, Con C&A2

2002/95/EC RoHS compliant

02 May. 10

QuartzCom AG
sales@quartzcom.com

QuartzCom Asia
sales-asia@quartzcom.com

QuartzCom USA
sales-usa@quartzcom.com

www.quartzcom.com

ISO 9001
BUREAU VERITAS
Certification

