

AU Power Cord with IEC Appliance Connector C19, V-Lock, straight

new



C19



70 °C

AS 3112



Description

- Power Cord, Protection class I, Pin temperature 70 °C,
- with V-Lock interlocking system

References

Weblinks

[pdf](#), [html](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Accessories](#)

Technical Data

| | |
|---------------------------|---|
| Ratings IEC | 16 A / 250 VAC; 50/60 Hz |
| Dielectric Strength | > 2 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz) |
| Allowable Operation Temp. | -25 °C to 75 °C |
| Degree of Protection | from front side IP 20 acc. to IEC 60529 |
| Protection Class | Suitable for appliances with protection class 1 acc. to IEC 61140 |
| Terminal | moulded |
| Material: Housing | PVC, black |

| | |
|-----------|---|
| Connector | C19 acc. to IEC/EN 60320-2-2 UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10A, Protection Class 1 |
|-----------|---|

Variants

| Connector | cable | | | | inlets | | | | | | Order Number |
|-----------|--------|--------------|-------|------------|-----------|---------|----------|-------------------------|----------|-------|--------------|
| Type | V-Lock | Cord Type | Color | Length [m] | Type | Country | Standard | Conductor cross section | Style | Index | |
| C19 | ● | H05VV-F3G1.5 | black | 2.0 | Australia | AU | AS 3112 | 3 x 1.5 mm ² | Straight | - | 6051.2050 |

Packaging unit

40 Pcs

Mating Inlets/Plugs

Category / Description

Appliance Inlet Overview complete



| | |
|---|------|
| IEC Appliance Inlet C20, Screw-on Mounting, Rear Side, PCB Terminal | 1601 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder, Quick-connect or Screw Terminal | 1621 |
| IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder, Quick-connect or Screw Terminal | 1624 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal | 4798 |

Appliance Inlet further types to VAC19KS



Power Entry Module Overview complete

| | |
|--|------|
| IEC Appliance Inlet C20 with Circuit Breaker TA35 1-pole | 6136 |
| IEC Appliance Inlet C20 with Line Switch, 1- or 2-pole | EC11 |
| IEC Appliance Inlet C20 with Circuit Breaker TA45 | EF11 |

Power Entry Module further types to VAC19KS

Category / Description

Power Entry Module with line filter [Overview complete](#)

| | |
|--|------|
| IEC Appliance Inlet C20 with Filter, Line Switch 2-pole | EC12 |
| IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed) | EF12 |

[Power Entry Module with line filter](#) further types to [VAC19KS](#)

Passende Stecker verriegelt zu

Appliance Inlet [Overview complete](#)

| | |
|---|------|
| IEC Appliance Inlet C20, Screw-on Mounting, Rear Side, PCB Terminal | 1601 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder, Quick-connect or Screw Terminal | 1621 |
| IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder, Quick-connect or Screw Terminal | 1624 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal | 4798 |

[Appliance Inlet](#) further types to [VAC19KS](#)

Power Entry Module [Overview complete](#)

| | |
|--|------|
| IEC Appliance Inlet C20 with Circuit Breaker TA35 1-pole | 6136 |
| IEC Appliance Inlet C20 with Line Switch, 1- or 2-pole | EC11 |
| IEC Appliance Inlet C20 with Circuit Breaker TA45 | EF11 |

[Power Entry Module](#) further types to [VAC19KS](#)

Power Entry Module with line filter [Overview complete](#)

| | |
|--|------|
| IEC Appliance Inlet C20 with Filter, Line Switch 2-pole | EC12 |
| IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed) | EF12 |

[Power Entry Module with line filter](#) further types to [VAC19KS](#)