

SERIES TL 3310 SWITCHES

TACT SWITCHES SMT - NORMALLY CLOSED

TACT SWITCHES

NAVIGATION SWITCHES

PUSHBUTTON SWITCHES

TOGGLE SWITCHES

ROCKER SWITCHES

SLIDE SWITCHES

SNAP-ACTION SWITCHES


DIP SWITCHES

KEYLOCK SWITCHES

ROTARY SWITCHES

DETECTOR SWITCHES

CAP OPTIONS



FEATURES & BENEFITS

- ▶ SMT tact
- ▶ Normally closed tact switch

APPLICATIONS/MARKETS

- ▶ Telecommunications
- ▶ Consumer Electronics
- ▶ Audio/visual
- ▶ Medical
- ▶ Testing/instrumentation
- ▶ Computer/servers/peripherals


SPECIFICATIONS

Contact Rating:	50mA @ 50 VDC
Life Expectancy:	100,000 cycles-F100 50,000 cycles-F200
Contact Resistance:	100mΩ max., typical @ 2-4 VDC
Insulation Resistance:	1000MΩ
Dielectric Strength:	250 VAC
Actuation Force:	100± 40 gf, 200± 50 gf
Operating Temperature:	-20°C to 70°C -30°C to 80°C
Travel:	0.3mm ± 0.15mm (100gf) 0.5mm ± 0.2mm (200gf)

MATERIALS

Housing:	Polyphenylene Sulfide (PPS)
Actuator:	Silicon Rubber
Cover:	Stainless Steel
Contacts:	Silver plated phosphor bronze
Terminals:	Silver plated brass strip

HOW TO ORDER



Example Ordering Number
TL-3310-A-F120-Q-G

Specifications subject to change without notice.

TL 3310

