

**Features**

- Center amplifying gate
- High surge current capability
- Low thermal impedance
- High speed performance




**Typical Applications**

- Inverters
- Choppers
- Induction heating
- All types of force-commutated converters

**Major Ratings and Characteristics**

Parameters	ST333S	Units
$I_{T(AV)}$	330	A
@ $T_C$	75	°C
$I_{T(RMS)}$	518	A
$I_{TSM}$ @ 50Hz	11000	A
@ 60Hz	11520	A
$I^2t$ @ 50Hz	605	KA <sup>2</sup> s
@ 60Hz	550	KA <sup>2</sup> s
$V_{DRM}/V_{RRM}$	400 to 800	V
$t_q$	15	μs
$T_J$	- 40 to 125	°C



## ST333S Series

Bulletin I25171 rev. D 03/03




International  
 Rectifier

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

Type number	Voltage Code	$V_{DRM}/V_{RRM}$ , maximum repetitive peak voltage V	$V_{RSM}$ , maximum non-repetitive peak voltage V	$I_{DRM}/I_{RRM}$ max. @ $T_J = T_{J\text{ max.}}$ mA
ST333S	04	400	500	50
	08	800	900	

#### Current Carrying Capability

Frequency							Units
	840	600	1280	1040	5430	4350	
50Hz	840	600	1280	1040	5430	4350	A
400Hz	650	450	1280	910	2150	1560	
1000Hz	430	230	1090	730	1080	720	
2500Hz	140	60	490	250	400	190	
Recovery voltage Vr	50	50	50	50	50	50	V
Voltage before turn-on Vd	$V_{DRM}$		$V_{DRM}$		$V_{DRM}$		
Rise of on-state current di/dt	50	50	-	-	-	-	A/µs
Case temperature	50	75	50	75	50	75	°C
Equivalent values for RC circuit	10Ω / 0.47µF		10Ω / 0.47µF		10Ω / 0.47µF		

#### On-state Conduction

Parameter	ST333S	Units	Conditions			
$I_{T(AV)}$ Max. average on-state current @ Case temperature	330	A	180° conduction, half sine wave			
	75	°C				
$I_{T(RMS)}$ Max. RMS on-state current	518	A	DC @ 63°C case temperature			
$I_{TSM}$ Max. peak, one half cycle, non-repetitive surge current	11000		t = 10ms	No voltage	Sinusoidal half wave, Initial $T_J = T_{J\text{ max}}$	
	11520		t = 8.3ms	reapplied		
	9250		t = 10ms	100% $V_{RRM}$		
	9700		t = 8.3ms	reapplied		
$I^2t$ Maximum $I^2t$ for fusing	605		KA <sup>2</sup> s	t = 10ms		No voltage
	550			t = 8.3ms		reapplied
	430			t = 10ms		100% $V_{RRM}$
	390	t = 8.3ms		reapplied		
$I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing	6050	KA <sup>2</sup> √s	t = 0.1 to 10ms, no voltage reapplied			

### On-state Conduction

Parameter	ST333S	Units	Conditions
$V_{TM}$ Max. peak on-state voltage	1.96	V	$I_{TM} = 1810A, T_J = T_J \text{ max}, t_p = 10\text{ms sine wave pulse}$
$V_{T(TO)1}$ Low level value of threshold voltage	0.91		$(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$
$V_{T(TO)2}$ High level value of threshold voltage	0.92		$(I > \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$
$r_{t1}$ Low level value of forward slope resistance	0.58	m $\Omega$	$(16.7\% \times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$
$r_{t2}$ High level value of forward slope resistance	0.58		$(I > \pi \times I_{T(AV)}), T_J = T_J \text{ max.}$
$I_H$ Maximum holding current	600	mA	$T_J = 25^\circ\text{C}, I_T > 30A$
$I_L$ Typical latching current	1000		$T_J = 25^\circ\text{C}, V_A = 12V, R_a = 6\Omega, I_G = 1A$

### Switching

Parameter	ST333S	Units	Conditions
di/dt Max. non-repetitive rate of rise of turned-on current	1000	A/ $\mu\text{s}$	$T_J = T_J \text{ max}, V_{DRM} = \text{rated } V_{DRM}$ $I_{TM} = 2 \times \text{di/dt}$
$t_d$ Typical delay time	1.0	$\mu\text{s}$	$T_J = 25^\circ\text{C}, V_{DM} = \text{rated } V_{DRM}, I_{TM} = 50A \text{ DC}, t_p = 1\mu\text{s}$ Resistive load, Gate pulse: 10V, 5 $\Omega$ source
$t_q$ Max. turn-off time	15		$T_J = T_J \text{ max}, I_{TM} = 550A, \text{commutating di/dt} = 40A/\mu\text{s}$ $V_R = 50V, t_p = 500\mu\text{s}, dv/dt = 200V/\mu\text{s}$

### Blocking

Parameter	ST333S	Units	Conditions
dv/dt Maximum critical rate of rise of off-state voltage	500	V/ $\mu\text{s}$	$T_J = T_J \text{ max. linear to } 80\% V_{DRM}, \text{ higher value available on request}$
$I_{RRM}$ $I_{DRM}$ Max. peak reverse and off-state leakage current	50	mA	$T_J = T_J \text{ max, rated } V_{DRM}/V_{RRM} \text{ applied}$

### Triggering

Parameter	ST333S	Units	Conditions
$P_{GM}$ Maximum peak gate power	60	W	$T_J = T_J \text{ max, } f = 50\text{Hz, } d\% = 50$
$P_{G(AV)}$ Maximum average gate power	10		
$I_{GM}$ Max. peak positive gate current	10	A	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$+V_{GM}$ Maximum peak positive gate voltage	20	V	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$-V_{GM}$ Maximum peak negative gate voltage	5		
$I_{GT}$ Max. DC gate current required to trigger	200	mA	$T_J = 25^\circ\text{C}, V_A = 12V, R_a = 6\Omega$
$V_{GT}$ Max. DC gate voltage required to trigger	3	V	
$I_{GD}$ Max. DC gate current not to trigger	20	mA	$T_J = T_J \text{ max, rated } V_{DRM} \text{ applied}$
$V_{GD}$ Max. DC gate voltage not to trigger	0.25		

## ST333S Series

Bulletin I25171 rev. D 03/03

International  
IR Rectifier

### Thermal and Mechanical Specifications

Parameter	ST333S	Units	Conditions
T <sub>J</sub> Max. junction operating temperature range	-40 to 125	°C	
T <sub>stg</sub> Max. storage temperature range	-40 to 150		
R <sub>thJC</sub> Max. thermal resistance, junction to case	0.10	K/W	DC operation
R <sub>thCS</sub> Max. thermal resistance, case to heatsink	0.03		Mounting surface, smooth, flat and greased
T Mounting torque, ± 10%	48.5 (425)	Nm (lbf-in)	Non lubricated threads
wt Approximate weight	535	g	
Case style	TO-209AE (TO-118)		See Outline Table

### $\Delta R_{thJC}$ Conduction

(The following table shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.011	0.008	K/W	T <sub>J</sub> = T <sub>J</sub> max.
120°	0.013	0.014		
90°	0.017	0.018		
60°	0.025	0.026		
30°	0.041	0.042		

### Ordering Information Table

Device Code								
1	2	3	4	5	6	7	8	9
ST	33	3	S	08	P	F	L	0
<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>	<b>9</b>
<b>1</b>	- Thyristor							
<b>2</b>	- Essential part number							
<b>3</b>	- 3 = Fast turn off							
<b>4</b>	- S = Compression bonding Stud							
<b>5</b>	- Voltage code: Code x 100 = V <sub>RRM</sub> (See Voltage Ratings table)							
<b>6</b>	- P = Stud base 3/4" 16UNF-2A							
<b>7</b>	- Reapplied dv/dt code (for t <sub>q</sub> test condition) F = 200V/μs							
<b>8</b>	- t <sub>q</sub> code (L = 15μs)							
<b>9</b>	- 0 = Eyelet terminals (Gate and Aux. Cathode Leads) 1 = Fast-on terminals (Gate and Aux. Cathode Leads)							
NOTE: For Metric Device M24 x 1.5 Contact Factory								

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics

# ST333S Series

Bulletin 125171 rev. D 03/03




Fig. 3 - On-state Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-repetitive Surge Current




Fig. 6 - Maximum Non-repetitive Surge Current




Fig. 7 - On-state Voltage Drop Characteristics




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristic




Fig. 9 - Reverse Recovered Charge Characteristics




Fig. 10 - Reverse Recovery Current Characteristics





Fig. 11 - Frequency Characteristics

# ST333S Series

Bulletin I25171 rev. D 03/03




Fig. 12 - Frequency Characteristics




Fig. 13 - Frequency Characteristics




Fig. 14 - Maximum On-state Energy Power Loss Characteristics




Fig. 15 - Gate Characteristics

Data and specifications subject to change without notice.  
 This product has been designed and qualified for Industrial Level.  
 Qualification Standards can be found on IR's Web site.