

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_SMA-50-1-6/111_Y



Description

Straight bulkhead cable feed through

Interface Standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact soldered
Weight 0.0035 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	MVQ (Silicone Rubber)
Fastening nut	Brass
Washer	Bronze

Surface Plating

Gold Plating (Nickel underplated)
SUCOPRO Plating
SUCOPRO Plating
SUCOPRO Plating
SUCOPRO Plating
SUCOPRO Plating

Related Documents

Outline drawing	DOU-00008985
Assembly instruction	DOC-0000185143
Mounting hole	DOU-00008731

Ordering Information

Bulk 100 pcs package 24_SMA-50-1-6/111_YH

Additional Information

Suitable cables EZ_47_TP_M17, SUCOFORM_47_CU, Quickform 47 PFA (Filotex)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions