


NTC Thermistors

Temperature sensor for measuring and control applications

Temperature range -55 °C + 125 °C
 Rated temperature +20 °C




Type	R ₂₀ Ω	Ordering code	Min. qty.	Max. qty.	Price each in DM				
					Min. qty. +	20 +	50 +	100 +	250 +
R_R tolerance ± 2 %									
■ K252/ 6 k/2%	6 k	Q63025-K2602-G	5	500	12,40	10,50	8,70	7,75	6,80
R_R tolerance ± 10 %									
■ K252/ 6 k/10%	6 k	Q63025-K2063-K	10	500	7,80	6,65	5,45	4,88	4,29
■ K252/ 40 k/10%	40 k	Q63025-K2044-K	10	500	7,80	6,65	5,45	4,88	4,29

Temperature sensor for measuring and control purposes, applicable in liquids and gases; e.g. for temperature measurement in flow-type heaters

Metal case, hermetically sealed

Temperature range -25 °C ... + 100 °C
 Rated temperature +25 °C
 Response time < 5 s



Type	R ₂₅ Ω	Ordering code	Min. qty.	Max. qty.	Price each in DM				
					Min. qty. +	10 +	20 +	50 +	100 +
R_R tolerance ± 2 %									
Z10/10 k/G	10 k	B57010-Z103-G	2	200	20,90	16,50	14,90	13,20	12,10