



2 X 6-32 UNC THREAD
V.172 MIN IN
INSERTS FOR TERMINAL
CONNECTION

NOTES
 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF $\phi .139$ MAX ON $1.000 \pm .002$ CENTERS
 2 - SEALED CONSTRUCTION PROVIDES SPLASH RESISTANCE
 3 - CUSTOMER PART NO. "018188E" AND LOGO "JACOBS U.S.A." ON OPPOSITE SIDE SHOWN
 4 - 2X TERMINAL SCREWS AND 2X WASHERS FURNISHED UNASSEMBLED
 5 - PER CUSTOMER PRINT REVISION "E"

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.



SCALE	FULL	SCALE PRINT
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		
ONE PLACE (.0)		$\pm .030$
TWO PLACE (.00)		$\pm .015$
THREE PLACE (.000)		$\pm .005$
ANGLES		\pm
WEIGHT		

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P N O

CHARACTERISTICS

OPERATING FORCE	18-26 OZ
DIFFERENTIAL FORCE	
RELEASE FORCE	4 OZ MIN
PRETRAVEL	
DIFFERENTIAL TRAVEL	.0008-.0035
OVERTRAVEL	.060 MIN
FREE POSITION	

REVISIONS

A	0000831
C.S.L.	10 JUL 03

CHECK

1 ISSUE



CATALOG LISTING

YZ-3RDS153-S

PAGE 1 OF 1

RELEASE NO. PR-19343-T REPLACES X93082-YZ

X93082-YZ

PTC/CAD 2D

DRAWN

C S L 10 JUL 03

CHECK

SAV

10 JUL 03

CHECK

10 JUL 03

CHECK

10 JUL 03

CHECK

10 JUL 03