## **MAIDA STYLE NUMBER**

## STANDARD SERIES

Electrical Specifications		
Continuous AC Voltage		VAC
Continuous DC Voltage		VDC
Maximum DC Leakage @ Rated VDC		uA
Low Varistor Voltage Limit		VDC
High Varistor Voltage Limit		VDC
Nominal Varistor Voltage		VDC
Current for Varistor Voltage		mΑ
Maximum Clamp Voltage		V
Maximum Clamp Voltage Test Current		Α
Peak Current Rating (1 Pulse)		Α
Peak Current Rating (2 Pulse)		Α
Energy Rating (8X20us)		J
Energy Rating (10X1000us)		J
Typical Capacitance		pF
Impulse Response Time	<	ns
Minimum Hipot of Coating		VDC
Minimum I.R. of Coating		$M\Omega$


Thermal	Spec	ificati	ions

Minimum Operating Temperature	°C
Maximum Operating Temperature	°C
Varistor Voltage Temperature Coeff	%/°C
Minimum Storage Temperature	°C
Maximum Storage Temperature	°C
Current/Energy Derating Above 85°C	%/°C



20 Libby Street P.O. Box 3529 Hampton, Virginia 23663 (757) 723-0785 Fax (757) 722-1194

Physical Specifications	
Lead Style	
Z Nominal	in.
Z Tolerance	in.
Lead Length Nominal	in.
Lead Length Tolerance	in.
Y Nominal	in.
Y Tolerance	in.
d Nominal	in.
Wire Gauge	AWG
Minimum Marking	
Nominal Disk Size	mm
D Maximum	in.
T Maximum	in.
H Maximum	in.



\* Contact Maida for a more detailed configuration drawing.

## Safety Agency Recognitions

UL 1449 File Number

UL 1414 File Number

UL 497B File Number

CSA File Number

**VDE File Number** 

SEV File Number