

Directional Coupler

ZADC-ED10203

Frequency MHz	Coupling dB		Mainline Loss dB			Directivity dB			VSWR (:1)	Power INPUT, W		
	$f_L - f_U$	Nom.	Flatness	L Typ. Max.	M Typ. Max.	U Typ. Max.	L Typ. Min.	M Typ. Min.		U Typ. Min.	Typ.	L Max.
400-2500	23.0±1.00			0.40			20		1.10			

L=low range(f_L to $10f_L$) M=mid range($10f_L$ to $f_U/2$) U=upper range($f_U/2$ to f_U)

SEE NOTES FOR CASE STYLE INFORMATION

Notes:

- For Surface Mount Environmental Specifications, please click [here](#). Re-flow soldering information is available in "[Surface Mount](#)" article.
- Non-catalog model. Please consult factory for price and delivery.
- Case style outline drawing: [99-01-587](#)
- General Quality Control Procedures and Environmental Specifications are given in [Mini-Circuits Guarantees Quality](#). Hi-Rel, MIL description are given in [Hi-Rel and MIL](#)
- Prices and Specifications subjects to change without notice.

Case Style - X0 (inch,mm) weight: 0 grams.

A	B	C	D	E	F	G	H	J
K	L	M	N	P	Q	R	S	T

Tolerance: .x ± .1 .xx ± .03 .xxx ± .015 inch.

FREQ (MHz)	I. Loss (dB) In-Out	Coupling (dB) In-CPL	Directivity (dB)	Return Loss (dB)		
				In	Out	CPL
400.00	0.32	23.80	20.07	17.07	27.01	16.62
440.00	0.34	23.77	20.64	17.92	27.44	17.38
480.00	0.30	23.71	21.25	18.82	27.82	18.08
520.00	0.33	23.68	21.63	19.57	28.16	18.70
560.00	0.30	23.61	21.97	20.17	28.46	19.33
600.00	0.31	23.58	22.54	20.90	28.75	19.93
640.00	0.30	23.53	22.88	21.53	28.97	20.47
680.00	0.31	23.48	23.17	21.93	29.19	20.99
720.00	0.31	23.43	23.50	22.48	29.41	21.57
760.00	0.31	23.38	23.72	23.17	29.61	22.11
800.00	0.31	23.33	24.00	23.40	29.77	22.63
850.00	0.33	23.27	24.42	23.91	29.93	23.38
900.00	0.32	23.19	24.51	24.65	30.36	24.00
960.00	0.34	23.13	24.92	25.01	30.70	24.60
1020.00	0.36	23.06	24.88	26.20	31.60	25.30
1080.00	0.35	22.98	25.10	25.89	32.06	25.44
1140.00	0.40	22.94	25.25	26.25	33.07	25.72
1200.00	0.41	22.87	24.90	25.15	33.74	25.55
1300.00	0.44	22.81	24.73	23.50	35.31	24.36

1400.00	0.47	22.75	24.25	22.54	36.91	22.63
1500.00	0.48	22.71	23.58	21.71	39.95	21.13
1600.00	0.50	22.71	22.77	21.20	45.84	19.81
1700.00	0.49	22.70	21.62	21.18	46.21	18.87
1760.00	0.60	22.73	20.86	20.98	42.67	18.41
1820.00	0.57	22.74	20.01	21.03	39.68	17.89
1880.00	0.67	22.78	19.12	20.70	37.33	17.51
1940.00	0.63	22.81	18.26	21.41	36.32	17.15
2000.00	0.65	22.89	17.37	21.12	34.49	16.89
2100.00	0.70	23.00	15.84	21.96	32.57	16.42
2200.00	0.80	23.09	14.27	22.93	30.50	16.32
2300.00	0.91	23.27	12.83	23.97	28.61	16.36
2400.00	0.93	23.42	11.44	25.98	27.41	16.42
2500.00	0.94	23.63	10.07	28.21	26.73	16.42



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE • 44-1252-832600 • Fax 44-1252-837010

ISO 9001 CERTIFIED

[Back](#)

i2 Technologies US, Inc.

HTML Pages converted to PDF Document

This document contains component information from the manufacturer's website which are not available in a revision controlled document from the manufacturer. To facilitate the addition of these parts into the Electronics Database, we are converting the HTML pages related to that part, from the manufacturer's website into Adobe PDF format. The contents of this document is based on the information provided on the manufacturer's website, therefore the information may have been changed by the manufacturer since this was created.

