


Wirewound Resistors, Commercial Power, Radial Terminals



FEATURES

- Direct mounting on printed circuit board
- Circuit board lock-in mounting tabs
- High performance for low cost
- Special inorganic potting compound and ceramic case provide high thermal conductivity in a fireproof package



RoHS
COMPLIANT

STANDARD ELECTRICAL SPECIFICATIONS			
GLOBAL MODEL (1)	POWER RATING $P_{40\text{ }^\circ\text{C}}$ W	RESISTANCE RANGE Ω $\pm 5\%, \pm 10\%$	WEIGHT (TYPICAL) g
CPR03...xx	3	0.1 - 1K	5.6
CPR05...xx	5	0.1 - 3.3K	6.6
CPR07...xx	7	0.1 - 5.7K	9.4
CPR10...xx	10	0.1 - 6.8K	10.0
CPR15...xx	15	0.1 - 6.8K	20.3
CPR20...xx	20	0.15 - 6.8K	25.6

Notes


(1) The xx is for the one or two digit "special" number as described in Global Part Number Information section.

TECHNICAL SPECIFICATIONS		
PARAMETER	UNIT	CPR RESISTOR CHARACTERISTICS
Temperature Coefficient	ppm/°C	± 600 below 1.0 Ω , ± 300 1.0 Ω and above
Short Time Overload	-	10 x rated power for 5 s
Terminal Strength	lb	10 minimum
Dielectric Withstanding Voltage	V_{AC}	1000
Maximum Working Voltage	V	$(P \times R)^{1/2}$
Operating Temperature Range	°C	- 65 to + 275

GLOBAL PART NUMBER INFORMATION																
Global Part Numbering Example: CPR0515R00JE5126																
C	P	R	0	5	1	5	R	0	0	J	E	5	1	2	6	
GLOBAL MODEL			VALUE			TOLERANCE			PACKAGING			SPECIAL				
CPR03 CPR05 CPR07 CPR10 CPR15 CPR20			R = Decimal K = Thousand R1500 = 0.15 Ω 1K500 = 1500 Ω			H = $\pm 3.0\%$ J = $\pm 5.0\%$ K = $\pm 10.0\%$			E51 = Lead (Pb)-free, bulk			CPRxx...21 = 10 mm, 2 pin CPRxx...26 = 25 mm, 2 pin CPR05...20 = 25 mm, 1 pin CPR07...13 = 10 mm, 1 pin CPR10...13 = 10 mm, 1 pin CPR15...13 = 10 mm, 1 pin CPR20...3 = 10 mm, 1 pin				



DIMENSIONS in inches [millimeters]



**TERMINAL STYLE 1
(SINGLE PIN)**

**TERMINAL STYLE 2
(DOUBLE PIN)**

GLOBAL MODEL	TERMINAL STYLE	DIMENSIONS in inches [millimeters]						
		L ± 0.040 [1.02]	W ± 0.031 [0.787]	H1 ± 0.031 [0.787]	H2 + 0.080 [2.03] - 0.040 [1.02]	D ± 0.005 [0.13]	P ± 0.060 [1.52]	R
CPR03...21	2	0.906 [23.01]	0.375 [9.53]	0.375 [9.53]	0.394 [10.0]	0.197 [5.00]	0.500 [12.70]	0.03 [0.75] Typ.
CPR03...26	2	0.906 [23.01]	0.375 [9.53]	0.375 [9.53]	0.984 [25.0]	0.197 [5.00]	0.500 [12.70]	
CPR05...20	1	1.060 [26.92]	0.375 [9.53]	0.360 [9.14]	0.984 [25.0]	-	0.590 [14.99]	
CPR05...21	2	1.060 [26.92]	0.375 [9.53]	0.360 [9.14]	0.394 [10.0]	0.197 [5.00]	0.590 [14.99]	
CPR05...26	2	1.060 [26.92]	0.375 [9.53]	0.360 [9.14]	0.984 [25.0]	0.197 [5.00]	0.590 [14.99]	
CPR07...13	1	1.398 [35.51]	0.375 [9.53]	0.360 [9.14]	0.394 [10.0]	-	0.886 [22.50]	
CPR07...21	2	1.398 [35.51]	0.375 [9.53]	0.360 [9.14]	0.394 [10.0]	0.197 [5.00]	0.886 [22.50]	
CPR07...26	2	1.398 [35.51]	0.375 [9.53]	0.360 [9.14]	0.984 [25.0]	0.197 [5.00]	0.886 [22.50]	
CPR10...13	1	1.888 [47.96]	0.375 [9.53]	0.360 [9.14]	0.394 [10.0]	-	1.380 [35.05]	
CPR10...21	2	1.888 [47.96]	0.375 [9.53]	0.360 [9.14]	0.394 [10.0]	0.197 [5.00]	1.380 [35.05]	
CPR10...26	2	1.888 [47.96]	0.375 [9.53]	0.360 [9.14]	0.984 [25.0]	0.197 [5.00]	1.380 [35.05]	
CPR15...13	1	1.888 [47.96]	0.500 [12.70]	0.500 [12.70]	0.394 + 0.080 - 0.130 [10.0 + 2.03 - 3.30]	-	1.280 [32.51]	
CPR15...21	2	1.888 [47.96]	0.500 [12.70]	0.500 [12.70]	0.394 + 0.080 - 0.130 [10.0 + 2.03 - 3.30]	0.197 [5.00]	1.280 [32.51]	
CPR15...26	2	1.888 [47.96]	0.500 [12.70]	0.500 [12.70]	1.181 [30.0]	0.197 [5.00]	1.280 [32.51]	
CPR20...3	1	2.498 [63.45]	0.500 [12.70]	0.500 [12.70]	0.300 + 0.080 - 0.130 [7.62 + 2.03 - 3.30]	-	1.870 [47.50]	
CPR20...21	2	2.498 [63.45]	0.500 [12.70]	0.500 [12.70]	0.300 + 0.080 - 0.130 [7.62 + 2.03 - 3.30]	0.197 [5.00]	1.870 [47.50]	
CPR20...26	2	2.498 [63.45]	0.500 [12.70]	0.500 [12.70]	1.181 [30.0]	0.197 [5.00]	1.870 [47.50]	

OTHER DIMENSIONS in inches [millimeters]					
CPR05...20, CPRxx...13, CPR20...3		CPRxx...21, CPR03...26, CPR05...26, CPR07...26, CPR10...26		CPR15...26, CPR20...26	
b	0.09 ± 0.01 [2.3 ± 0.25]	b	0.06 ± 0.01 [1.5 ± 0.25]	b	0.06 ± 0.01 [1.5 ± 0.25]
c	0.09 ± 0.01 [2.3 ± 0.25]	c	0.06 ± 0.01 [1.5 ± 0.25]	c	0.06 ± 0.01 [1.5 ± 0.25]
d	0.053 ± 0.005 [1.35 ± 0.127]	d	0.045 ± 0.005 [1.14 ± 0.127]	d	0.045 ± 0.005 [1.14 ± 0.127]
f	0.020 ± 0.001 [0.51 ± 0.025]	f	0.020 ± 0.001 [0.50 ± 0.025]	f	0.020 ± 0.001 [0.50 ± 0.025]
g	0.287 ± 0.005 [7.30 ± 0.127]	g	0.287 ± 0.005 [7.30 ± 0.127]	g	0.394 ± 0.005 [10.0 ± 0.127]
h	0.055 ± 0.005 [1.40 ± 0.127]	h	0.078 ± 0.005 [2.0 ± 0.127]	h	0.078 ± 0.005 [2.0 ± 0.127]
j	0.18 ± 0.01 [4.5 ± 0.25]	i	0.059 ± 0.005 [1.50 ± 0.127]	i	0.059 ± 0.005 [1.50 ± 0.127]
		j	0.197 ± 0.01 [5.0 ± 0.25]	j	0.197 ± 0.01 [5.0 ± 0.25]

MATERIAL SPECIFICATIONS


Element: Copper-nickel alloy or nickel-chrome alloy, depending on resistance value

Core: Woven fiberglass

Body: Steatite ceramic case with inorganic potting compound

Terminals: Tin plated CRS

Part Marking: DALE, model, wattage, value, tolerance, date code



PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS
Thermal Shock	- 25 °C to + 155 °C, 5 cycles, 30 min dwell time	± (1.0 % + 0.05 Ω) ΔR
Short Time Overload	10 x rated power for 5 s	± (2.0 % + 0.05 Ω) ΔR
Dielectric Withstanding Voltage	1000 V _{rms} for 1 min	± (2.0 % + 0.05 Ω) ΔR
Low Temperature Operation	- 65 °C, full rated working voltage for 45 min	± (3.0 % + 0.05 Ω) ΔR
Humidity	75 °C, 90 % - 100 % RH, 240 h	± (5.0 % + 0.05 Ω) ΔR
Load Life	1000 h at rated power, + 40 °C, 1.5 h "ON", 0.5 h "OFF"	± (5.0 % + 0.05 Ω) ΔR
Terminal Strength	10 pounds in axial direction for 30 s	± (2.0 % + 0.05 Ω) ΔR
Resistance to Solder Heat	Terminal immersed 3.5 s in molten solder at 1/8" to 3/16" from body	± (1.0 % + 0.05 Ω) ΔR



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.