



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468

8	COVER	NOTE 2	NOTE 3	1	CV-523X06-T
7	FERRULE	COPPER	NOTE 3	1	FR-648/533X127C
6	CONTACT PIN	NOTE 1	NOTE 4	1	RFU-600-10C1-8
5	SHELL	NOTE 1	NOTE 3	1	PT-4000-002-1
4	RETAINER RING	SUS 304	NATURAL	1	PT-4000-002-6-B
3	INSULATOR	NOTE 5	NATURAL	1	RFU-600-10C1-7
2	BODY	NOTE 1	NOTE 3	1	BD19AAJ01A
1	HOUSING	NOTE 1	NOTE 3	1	HS00ACU01A
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED TOLERANCES
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

PART NO.	MU1112A1-NT3G-1-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'
FILE NO.	

Amphenol	
TITLE	MINI UHF R/A CRIMP PLUG (FOR RG-58/U,58C/U)
DRAWING NO.	KJ-MU1112A1-NT3G-58U-50
ITEM NO.	