

.050" x .050" SOCKETS FOLC SERIES

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com/FOLC

Insulator Material:

Black Liquid Crystal Polymer

Contact Material:

BeCu

Current Rating:

1A @ 80°C ambient

Operating Temp Range:

-55°C to +125°C

Plating:

Au, PdNi or Sn over 50µ" (1,27µm) Ni

Contact Resistance:

15 mΩ max

Insertion Depth:

(3,30mm) .130" to

(4,06mm) .160"

Insertion Force:

(Single contact only)

Standard= 5.0oz (1,39N) avg;

LIF= 2.0oz (0,56N) avg.

Normal Force:

Standard= 70 grams

(0,69N) avg; LIF= 40 grams

(0,39N) avg.

Withdrawal Force:

(Single contact only)

Standard= 4oz (1,11N) avg;

LIF= 1.5oz (0,42N) avg.

Max Cycles:

100 with 30µ" (0,76µm) Au

RoHS Compliant:

Yes

Processing:

Max Processing Temp:

230°C for 60 seconds, or

260°C for 20 seconds 3x

Lead-Free Solderable:

Yes

SMT Lead Coplanarity:

(0,15mm) .006" max

Mates with:
MOLC




APPLICATION SPECIFIC OPTION

Alignment pins available.
Call Samtec.

Low Insertion Force
contacts available

High reliability
Tiger-Eye
contacts



FOLC

1

NO. PINS
PER ROW

LEAD
STYLE

PLATING
OPTION

Q

OPTION

20, 25, 30, 35,
40, 45, 50
(Call Samtec for other sizes)

-01 & -04
= Through-Hole

-M1 & -M2
= Mixed Technology

-L1 & -L4
= Low Insertion Force
Through-Hole



-S

= 30µ" (0,76µm)
Gold on contact,
Matte Tin on tail

-P

= Gold flash over
30µ" (0,76µm)
PdNi on contact,
Matte Tin on tail
(-01 & -04 only)

-LC
= Locking
Clip



LEAD STYLE	C
-01, -M1	(1,91) .075
-04, -M2	(3,04) .120

Note: Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047
 SAMTEC GERMANY • Tel: +49 (0) 89/89460-0 • Fax: +49 (0) 89/89460-299
 SAMTEC SCANDINAVIA • Tel: +46-84477280 • Fax: +46-87420413
 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502
 SAMTEC HONG KONG • Tel: 852-26904858 • Fax: 852-26904842
 SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520
 SAMTEC FRANCE • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61
 SAMTEC ISRAEL • Tel: 972-3-7526600 • Fax: 972-3-7526690
 SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-53854047
 SAMTEC SOUTH AFRICA • Tel: 27 11 4528112 • Fax: 27 86 6714432
 SAMTEC UK • Tel: 01236 739292 • Fax: 01236 727113
 SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315
 SAMTEC INDIA • Tel: 91 80 306 21 612 • Fax: 91 80 4152 8187
 SAMTEC TAIWAN • Tel: 886 02 2698-3367 • Fax: 886 02 8698-2159
 SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745