

Engineering Development Model

Voltage Controlled Oscillator

JCOS-ED6304A/2

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE : BG419

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Typ.	Max.	Units
Frequency	773		917	MHz
Tuning Voltage	1		8	V
Power Output		+8		dBm
Phase Noise	at 1 kHz offset	-87		dBc/Hz
	at 10 KHz offset	-111		dBc/Hz
	at 100 KHz offset	-131		dBc/Hz
	at 1000 kHz offset	-150		dBc/Hz
Pulling at 12 dBr PK-PK all phases		2.7		MHz
Pushing at Vcc=5V±0.25V		0.5		MHz/V
Tuning Sensitivity		22 - 27		MHz/V
Harmonic Suppression		-36		dBc
3 dB Modulation Bandwidth		2000		kHz
Supply Voltage		5		V
Supply Current			30	mA

MAXIMUM RATINGS	
Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Supply Voltage (Vcc)	+7V
Absolute Tuning Voltage (Vtune)	+10V

PIN CONNECTIONS	
RF OUT	10
VCC	14
V-TUNE	1
GROUND	2,3,4,5,6,9,10,11,12,13,14