

FEATURES

- SURFACE MOUNTABLE BY I.R. REFLOW SOLDER
- SMALL SIZE FLAT CERAMIC PACKAGE:
7.6 x 12.7 x 3 mm
- OPTICAL OUTPUT POWER:
 $P_f = 0.2 \text{ mW}$
- PEAK WAVELENGTH:
 $\lambda_c = 1310 \text{ nm}$
- WIDE OPERATING TEMPERATURE RANGE:
-40 to +85°C
- INTERNAL InGaAs MONITOR PD
- DETACHABLE PIGTAIL INTERFACE

DESCRIPTION

The OD-8306N is a new surface mount low cost 1310 nm LD module. This device can achieve stable operation over a wide temperature range of -40 to +85°C. An InGaAs PIN monitor photodiode is built in for APC (Automatic Power Control) circuit. This module has a detachable pigtail interface and is packaged in an 8 pin surface mount package, allowing the module to be soldered like an ordinary IC by the standard I.R. reflow soldering process. OD-8306N can be operated at speeds up to 622 Mb/s and is especially suitable for the use of the subscriber loop, SONET and FITL.

APPLICATIONS

- SUBSCRIBER LOOP
- TELECOMMUNICATIONS
- DATA COMMUNICATIONS
- LOCAL AREA NETWORKS

ELECTRO-OPTICAL CHARACTERISTICS ($T_c = +25^\circ\text{C}$, unless otherwise specified)

PART NUMBER		OD-8306N		
SYMBOLS	PARAMETERS AND CONDITIONS ¹	UNITS	MIN	TYP
P_f	Optical Output Power from Fiber Pigtail End, CW, $T_c = -40$ to $+85^\circ\text{C}$	mW	0.2	
I_{TH}	Threshold Current $T_c = -40$ to $+85^\circ\text{C}$	mA	3 1	8 — 40
I_{MOD}	Modulation Current $T_c = -40$ to $+85^\circ\text{C}$	mA	5 4	13 — 20 40
P_{TH}	Threshold Output Power at CW, $I_F = I_{TH}$ ²	μW	—	— 8
V_{OP}	Forward Voltage, CW, $P_f = 0.2 \text{ mW}$	V	—	1.2 1.5
S_e	Slope Efficiency $T_c = -40$ to $+85^\circ\text{C}$	mW/mA	0.010 0.005	0.015 — 0.040 0.050
λ_c	Central Wavelength, CW, $P_f = 0.2 \text{ mW}$, RMS (-20 dB) $T_c = -40$ to $+85^\circ\text{C}$	nm	1290 1260	1310 — 1330 1360
$\Delta\lambda/\Delta T$	Temperature Dependency of Central Wavelength, $T_c = -40$ to $+85^\circ\text{C}$	nm/ $^\circ\text{C}$	—	0.4 0.5
σ	Spectral Width, CW, $P_f = 0.2 \text{ mW}$, RMS (-20 dB) $T_c = -40$ to $+85^\circ\text{C}$	nm	—	1 — 2.5 4
f_c	Cut-off Frequency at -3dB	GHz	—	2.0 —
t_r	Rise Time $I_B = I_{TH}, 10\text{-}90\%$	nsec	—	0.2 0.5
t_f	Fall Time $I_B = I_{TH} 90\text{-}10\%$	nsec	—	0.3 0.5
I_M	Monitor Current (PD) CW, $P_f = 0.2 \text{ mW}$, $V_R = 5 \text{ V}$	μA	200	700 1600
I_D	Dark Current (PD) $V_R = 5 \text{ V}$	μA	—	0.001 0.1
C_t	Capacitance (PD) $V_R = 5 \text{ V}$, $f = 1 \text{ MHz}$	pF	—	6 20
Er	Tracking Error ³ $I_m = \text{const}$, $T_c = -40$ to $+85^\circ\text{C}$	dB	0	0.5 1.5

Notes:

1. Connected with multimode (G150) fiber pigtail (OD-S524 Series).
2. If: Forward Current of LD.

$$3. Er = \left| 10 \cdot \log \frac{P_f(T_c)}{P_f(25^\circ\text{C})} \right| \text{ max.}$$





ABSOLUTE MAXIMUM RATINGS¹

(TA = 25°C, unless otherwise specified)



SYMBOLS	PARAMETERS	UNITS	RATINGS
Pf	Fiber Output Power	mW	0.4
VR (LD)	Laser Reverse Voltage	V	2.0
If(PD)	Monitor Forward Current	mA	2.0
VR (PD)	Monitor Reverse Voltage	V	20
TOP	Operating Temperature	°C	-40 to +85
TSTG	Storage Temperature	°C	-40 to +85
Tsol	Lead Soldering Temperature ²	°C	230

Notes:



1. Operation in excess of any one of these parameters may result in permanent damage.
2. 30 seconds, reflow soldering.

TYPICAL PERFORMANCE CURVES**FIBER OUTPUT POWER vs.
FORWARD CURRENT****THRESHOLD CURRENT vs.
CASE TEMPERATURE****TRACKING ERROR CHARACTERISTICS****SLOPE EFFICIENCY vs.
CASE TEMPERATURE**

TYPICAL PERFORMANCE CURVES



OUTLINE DIMENSIONS (Units in mm)



PIN	FUNCTION
1	NC
2	Package Ground
3	NC
4	PD Cathode
5	PD Cathode
6	LD Anode
7	LD Cathode
8	NC