SMB Termination

 50Ω


DC to 6000 MHz

Maximum Ratings

Operating Temperature -55°C to 100°C
Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch)

wt	D	В	Α
grams	0.33	0.36	0.55
4.0	8.38	9.14	13.97

Features

- SMB connector with female center contact
- wideband, DC to 6000 MHz
- rugged construction

Applications

- · cellular communications
- test set-up
- instrumentation
- PCS

ROSE-50+



CASE STYLE: LL604

Connectors	Model	Price	Qty.
SMB-FEM	ROSE-50(+)	\$9.95 ea.	(1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.


Electrical Specifications

FREQUENCY (MHz)	IMPEDANCE (OHMS)	RETURN LOSS (dB) MIN.	POWER RATING* (W)
		DC-2 DC-4 DC-6 GHz GHz GHz	
DC-6000	50	30 23 20	0.50

^{*}At 70°C, derate linearly at 0.005W/°C to .35W at 100°C.

Typical Performance Data

Frequen (MHz)		
1.0	0 69.84	
100.0	0 70.87	
200.0	0 65.00	
500.0	0 50.04	
1000.0	0 49.61	
2000.0	0 45.48	
3000.0	0 47.04	
4000.0	0 35.88	
5000.0	0 28.01	
6000.0	0 24.18	





For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicipality.com