

TWO-PIN POLARIZED 30/330 SERIES TWBNC/TWTNC Mil-C-3655 Interface

CABLE PLUG
TWTNC POSITIVE ALIGNING
TWO-PIN POLARIZED

PLPA330

CIRCUIT BOARD BULKHEAD JACK
RIGHT ANGLE-TWO-PIN
POLARIZED TWINAX (TWBNC)

CBBJR39A
Mounting Hole: D3.125

CABLE PLUG
WRENCH CRIMP, TWO-PIN POLARIZED

2-lug Threaded

PL330-⚠
PL330-⚠

BULKHEAD JACK
FRONT MOUNT, SOLDER POT
TWO-PIN POLARIZED

2-lug Threaded

BJ30
BJ330

Mounting Hole: D5.130

BULKHEAD JACK
REAR MOUNT, SOLDER POT
TWO-PIN POLARIZED

2-lug Threaded

BJ31
BJ331

Mounting Hole: D3.280

FEED-THROUGH JACK
TWO-PIN POLARIZED

2-lug Threaded

BJ38
BJ338

Mounting Hole: D3.160

BULKHEAD CABLE JACK
REAR MOUNT, WRENCH CRIMP
TWO-PIN POLARIZED

2-lug Threaded

BJ39-⚠
BJ339-⚠

Mounting Hole: D3.218

⚠ - Refers to Cable Group Table, see pages 68-88. "D" mounting holes are on page 45. Note: Only 30/330 Series have two-pin polarizations.