

CRYSTAL FILTERS

10.7MHz, 21.4MHz Series

BUILT-IN TRANSFORMER TYPE MCF

An integrated MCF with a matching transformer added as a corrective measure.

■ Features

- Can be manufactured with desired terminating impedance
- No adjustment needed
- Stable temperature characteristics

■ 10.7MHz, 21.4MHz Series

※ -40~+80°C(Available on request)

Model	Nominal Frequency (MHz)	Pole	Pass Bandwidth		Attenuation Bandwidth				Ripple (dB)	Insertion Loss (dB)	Terminating Impedance (Ω// pF)	Operating Temp. Range *(°C)	Type	Weight (g)
			(dB)	(kHz)	(dB)	(kHz)	(dB)	(kHz)						
10A7.5CA	10.7	6	3	±3.75	45	±8.75	65	±12.5	2	3.5	910// 25	-20~+70	D-152	23
10A12CA	10.7	6	3	±6	45	±14	65	±20	2	3	910// 25	-20~+70	D-152	23
10A15CA	10.7	6	3	±7.5	45	±17.5	65	±25	2	3	910// 25	-20~+70	D-152	23
10A30CA	10.7	6	3	±15	45	±35	65	±50	2	3	910// 25	-20~+70	D-152	23
10A7.5DA	10.7	8	3	±3.75	70	±8.75	90	±12.5	2	4	910// 25	-20~+70	D-152	25
10A12DA	10.7	8	3	±6	70	±14	90	±20	2	3.5	910// 25	-20~+70	D-152	25
10A15DA	10.7	8	3	±7.5	70	±17.5	90	±25	2	3.5	910// 25	-20~+70	D-152	25
10A30DA	10.7	8	3	±15	70	±35	80	±50	2	3.5	910// 25	-20~+70	D-152	25
10B7.5DA	10.7	8	3	±3.75	70	±8.75	90	±12.5	2	4	910// 25	-20~+70	D-153	25
10B12DA	10.7	8	3	±6	70	±14	90	±20	2	3.5	910// 25	-20~+70	D-153	25
10B15DA	10.7	8	3	±7.5	70	±17.5	90	±25	2	3.5	910// 25	-20~+70	D-153	25
10B30DA	10.7	8	3	±15	70	±35	80	±50	2	3.5	910// 25	-20~+70	D-153	25
10P7.5DA	10.7	8	3	±3.75	70	±8.75	90	±12.5	2	4	910// 25	-20~+70	D-100	32
10P12DA	10.7	8	3	±6	70	±14	90	±20	2	3.5	910// 25	-20~+70	D-100	32
10P15DA	10.7	8	3	±7.5	70	±17.5	90	±25	2	3.5	910// 25	-20~+70	D-100	32
10P30DA	10.7	8	3	±15	70	±35	80	±50	2	3.5	910// 25	-20~+70	D-100	32
21A7.5CB	21.4	6	3	±3.75	45	±8.75	65	±12.5	2	4.5	910// 15	-20~+70	D-152	23
21A12CB	21.4	6	3	±6	45	±14	65	±20	2	3.5	910// 15	-20~+70	D-152	23
21A15CB	21.4	6	3	±7.5	45	±17.5	65	±25	2	3.5	910// 15	-20~+70	D-152	23
21A30CB	21.4	6	3	±15	45	±35	65	±50	2	3.5	910// 15	-20~+70	D-152	23
21A7.5DB	21.4	8	3	±3.75	70	±9	90	±12.5	2	5	910// 15	-20~+70	D-152	25
21A12DB	21.4	8	3	±6	70	±14	90	±20	2	4	910// 15	-20~+70	D-152	25
21A15DB	21.4	8	3	±7.5	70	±17.5	90	±25	2	4	910// 15	-20~+70	D-152	25
21A30DB	21.4	8	3	±15	70	±35	80	±50	2	4	910// 15	-20~+70	D-152	25
21P7.5DA	21.4	8	3	±3.75	70	±9	90	±12.5	2	5	910// 25	-20~+70	D-100	32
21P12DA	21.4	8	3	±6	70	±14	90	±20	2	4	910// 25	-20~+70	D-100	32
21P15DA	21.4	8	3	±7.5	70	±17.5	90	±25	2	4	910// 25	-20~+70	D-100	32
21P30DA	21.4	8	3	±15	70	±35	80	±50	2	4	910// 25	-20~+70	D-100	32
21C7.5DC	21.4	8	3	±3.75	65	±9	90	±12.5	2	4.5	470// 15	-20~+70	D-162	12
21C12DC	21.4	8	3	±6	65	±14	90	±20	2	4	470// 15	-20~+70	D-162	12
21C15DC	21.4	8	3	±7.5	65	±17.5	90	±25	2	4	470// 15	-20~+70	D-162	12
21C30DC	21.4	8	3	±15	65	±35	80	±50	2	4	470// 15	-20~+70	D-162	12

10.7MHz, 21.4MHz Series

BUILT-IN TRANSFORMER TYPE MCF

