

A technical line drawing of a cable assembly. The cable is long and flexible, forming a large loop. At each end, there is a connector. The connector on the left is labeled 'ST CONNECTOR' with a leader line pointing to it. The connector on the right is a different type, possibly a BNC or similar, and is also indicated by a dashed line and an arrow. The cable has a braided shield section near the left connector.

1. SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE PACKAGE QUANTITY.
2. CONSTRUCTED WITH 9/125 MICRON SINGLEMODE CABLE AND A ZIRCONIA SPLIT SLEEVE.
3. EXTRA SPLIT SLEEVES ARE PROVIDED AS REPLACEMENTS.
4. PATCHCORD LENGTH IS 20.3 cm [8"].
5. ALL MATERIALS AND COMPONENTS USED MUST MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTIONS OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

INTERFACE
FOR CONNECTION TO PRE-POLISHED
CONNECTOR WITH 2.50mm FERRULE

ST CONNECTOR
FOR CONNECTION TO V.F.L. UNIT

