

## Standard FSJ/LDF/ETS Cable Assemblies - Ordering Information

Connectors	Lengths, feet	Type No.
<b>FSJ1-50A Cable</b>		
N Male/N Male, premium	6, 8 or variable	F1-PNMNM-(* )
N Male/Right Angle N Male, premium	6, 8 or variable	F1-PNMNR-(* )
N Male/N Female, premium	6, 8 or variable	F1-PNMNF-(* )
N Male/UHF Male, premium	6, 8 or variable	F1-PNMUM-(* )
N Male/BNC Male, premium	6, 8 or variable	F1-PNMBM-(* )
N Male/SMA Male, premium	6, 8 or variable	F1-PNMMSM-(* )
UHF Male/UHF Male	6, 8 or variable	F1-UMUM-(* )
UHF Male/Mini UHF Male	6, 8 or variable	F1-UMMU-(* )
BNC Male/BNC Male, premium	6, 8 or variable	F1-PBMBM-(* )
BNC Male/SMA Male, premium	6, 8 or variable	F1-PBMSM-(* )
SMA Male/SMA Male, premium	6, 8 or variable	F1-PSMSM-(* )
SMA Male/SMA Female, premium	6, 8 or variable	F1-PSMSF-(* )
SMA Male/Right Angle SMA Male, premium	6, 8 or variable	F1-PSMSR-(* )
<b>FSJ2-50 Cable</b>		
N Male/N Male, premium	6, 8 or variable	F2-PNMNM-(* )
N Male/7-16 DIN Male	6, 8 or variable	F2-PNMMDM-(* )
7-16 DIN Male/7-16 DIN Male	6, 8 or variable	F2-PDMDM-(* )
<b>FSJ4-50B Cable</b>		
N Male/N Male	3, 6, 8 or variable	F4-NMNM-(* )
N Male/N Male, premium	6, 8 or variable	F4-PNMNM-(* )
N Male/Right Angle N Male	6, 8 or variable	F4-NMNR-(* )
N Male/N Female	6, 8 or variable	F4-NMNF-(* )
N Male/UHF Male	6, 8 or variable	F4-NMUM-(* )
N Male/7-16 DIN Male	6, 8 or variable	F4-PNMMDM-(* )
UHF Male/UHF Male	6, 8 or variable	F4-UMUM-(* )
7-16 DIN Male/7-16 DIN Male	6, 8 or variable	F4-PDMDM-(* )
<b>FSJ4P-50B-4, Low-VSWR Cable (800 - 960 MHz) - See specifications on page 452.</b>		
N Male/N Male	3, 6, 10, 15, 20, 25, 30 or variable	F4P4-NMNM-(* )
N Male/Right Angle N Male	10, 15, 20, 25, 30 or variable	F4P4-NMNR-(* )
<b>EFX2-50 Cable</b>		
N Male/N Male, premium	6, 8 or variable	EFX2-PNMNM-(* )
N Male/7-16 DIN Male	6, 8 or variable	EFX2-PNMMDM-(* )
7-16 DIN Male/7-16 DIN Male	6, 8 or variable	EFX2-PDMDM-(* )
<b>LDF2-50 Cable</b>		
N Male/N Male	6, 8 or variable	L2-NMNM-(* )
N Male/N Female	6, 8 or variable	L2-NMNF-(* )
N Male/UHF Male	6, 8 or variable	L2-NMUM-(* )
UHF Male/UHF Male	6, 8 or variable	L2-UMUM-(* )
N Male/7-16 DIN Male	6, 8 or variable	L2-PNMMDM-(* )
7-16 DIN Male/7-16 DIN Male	6, 8 or variable	L2-PDMDM-(* )
<b>LDF4-50A Cable</b>		
N Male/N Male	3, 6, 8 or variable	L4-NMNM-(* )
N Male/N Male, premium	6, 8 or variable	L4-PNMNM-(* )
N Male/Right Angle N Male	6, 8 or variable	L4-NMNR-(* )
N Male/N Female	6, 8 or variable	L4-NMNF-(* )
N Male/UHF Male	6, 8 or variable	L4-NMUM-(* )
N Male/7-16 DIN Male	6, 8 or variable	L4-PNMMDM-(* )
UHF Male/N Female	6, 8 or variable	L4-UMNF-(* )
UHF Male/UHF Male	6, 8 or variable	L4-UMUM-(* )
7-16 DIN Male/7-16 DIN Male	6, 8 or variable	L4-PDMDM-(* )
<b>LDF4P-50A-1, Low-VSWR Cable (824 - 960 MHz) - See specifications on page 463.</b>		
N Male/N Male	3, 6, 10 or variable	L4P1-NMNM-(* )

\* Insert length in feet for the listed standard lengths. For other lengths, specify base Type No. and length in feet or meters. e.g., F1-PNMNM, 15 feet long.  
For configurations not listed, contact Andrew.