





| PART NR. | L1 | L2 | L3 | |
|--------------|-----|-------|-------|-----------|
| HM2H05PILF | 3.0 | 13.45 | 11.15 | AVAILABLE |
| HM2H05PI09LF | 3.9 | 14.35 | 12.05 | AVAILABLE |
| HM2H05PI15LF | 4.5 | 14.95 | 12.65 | AVAILABLE |
| HM2H05PI17LF | 4.7 | 15.15 | 12.85 | AVAILABLE |
| HM2H05PI19LF | 4.9 | 15.35 | 13.05 | AVAILABLE |
| HM2H05PI22LF | 5.2 | 15.65 | 13.35 | AVAILABLE |
| HM2H05PI30LF | 6.0 | 16.45 | 14.15 | AVAILABLE |

- NOTES:
1. MEASURED AT THE BOTTOM
 2. MATERIAL: GLASSREINFORCED POLYESTER UL94 - V0
 3. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIONS AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
 4. THE PRODUCT IS NOT INTENDED TO BE EXPOSED TO A MANUFACTURING SOLDER PROCESS.

| rev | ecn no | dr | date |
|-----|---------------------------|-----|----------|
| A | CONVERSION REVISION DS | KN | 13-09-01 |
| B | DG06-0536 | KL | 12-13-06 |
| 05 | BEC 9. 3434 | T.C | 26-10-98 |
| 04 | MARKING ADDED | M.F | 22-09-98 |

| | | | | | | | | | | | |
|---------------------------------------------------------------------------------------|--|--------------------|--|---------------------------------------------------------------------------------------|--|---------------------------------------------------------------------|--|---------------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------|-----------|
|  | | www.fciconnect.com | |  | | tolerance IDEC ±0.2 IDEC 2DEC ±0.1 2DEC ANGLES ± 1° HOEKEN | |  | |  | |
| Dr | | W. P. | | 280294 | | Product family | | size | | A4 | |
| Eng | | | | | | Spec ref | | | | Scale | |
| Chr | | | | | | Material | | | | 1/3 | |
| Appr | | | | | | | | ECN | | | |
| title HM2 REAR HEADER WITH LOCKING DEVICE (125 POS) | | | | | | dwg no BS, C , 201630, 018 | | | | | Rev. B |
| catalog no HM2H05PI--LF | | | | | | CUSTOMER | | | | sheet 1 of 1 | |