




# PANDUIT® REEL SMART™ Termination System

## TERMO™ – Ring Terminals, Nylon Insulated

- Funnel Entry
- Metal Insulation Grip Sleeve





PANDUIT® Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				CA9 Series Crimp Die	CA-800 Series Crimp Die	Pieces Per Reel
					A	W	C	G			
<b>PNF18-4R-3K</b>	22-18 .03 Stock	Red	.145	#4	.78	.25	.21	.65	CD9-1A	CD-800-1	3000
<b>PNF18-4RN-3K</b>				#4	.74	.22	.19	.63			3000
<b>PNF18-6R-3K</b>				#6	.78	.25	.21	.65			3000
<b>PNF18-6RN-3K</b>				#6	.74	.22	.16	.63			3000
<b>PNF18-8R-3K</b>				#8	.86	.31	.25	.70			3000
<b>PNF18-10R-3K</b>				#10	.86	.31	.25	.70			3000
<b>PNF18-14R-3K</b>	1/4"	1.06	.46	.38	.84	3000					
<b>PNF14-4R-3K</b>	16-14 .03 Stock	Blue	.162	#4	.78	.25	.18	.66	CD9-2A	CD-800-2	3000
<b>PNF14-6R-3K</b>				#6	.87	.31	.24	.71			3000
<b>PNF14-6RN-3K</b>				#6	.78	.25	.18	.63			3000
<b>PNF14-8R-3K</b>				#8	.87	.31	.25	.71			3000
<b>PNF14-10R-3K</b>				#10	.85	.31	.29	.71			3000
<b>PNF14-14R-3K</b>				1/4"	1.06	.46	.40	.85			3000
<b>PNF10-6R-2K</b>	12-10 .04 Stock	Yellow	.225	#6	1.04	.38	.31	.86	CD9-3B	CD-800-3	2000
<b>PNF10-8R-2K</b>				#8	1.04	.38	.31	.86			2000
<b>PNF10-10R-2K</b>				#10	1.04	.38	.31	.86			2000
<b>PNF10-14R-2K</b>				1/4"	1.19	.52	.38	.93			2000
<b>PNF10-56R-2K</b>				5/16"	1.19	.52	.38	.93			2000
<b>PNF10-38R-2K</b>				3/8"	1.27	.58	.43	.98			2000

Order number of pieces required, in multiples of standard reel quantity. *Prime items appear in BOLD.*

## TERMO — Ring Terminals, Nylon Insulated

- Metal Insulation Grip Sleeve




PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				CA9 Series Crimp Die	CA-800 Series Crimp Die	Pieces Per Reel
					A	W	C	G			
<b>PN18-4R-3K</b>	22-18 .03 Stock	Red	.136	#4	.80	.25	.22	.67	CD9-1A	CD-800-1	3000
<b>PN18-6R-3K</b>				#6	.78	.25	.22	.67			3000
<b>PN18-6RN-3K</b>				#6	.74	.22	.18	.63			3000
<b>PN18-8R-3K</b>				#8	.86	.31	.25	.70			3000
<b>PN18-10R-3K</b>				#10	.86	.31	.25	.70			3000
<b>PN18-14R-3K</b>				1/4"	1.05	.45	.38	.83			3000
<b>PN14-4R-3K</b>	16-14 .03 Stock	Blue	.162	#4	.76	.25	.22	.65	CD9-2A	CD-800-2	3000
<b>PN14-6R-3K</b>				#6	.86	.31	.25	.70			3000
<b>PN14-6RN-3K</b>				#6	.76	.25	.22	.65			3000
<b>PN14-8R-3K</b>				#8	.86	.31	.25	.70			3000
<b>PN14-10R-3K</b>				#10	.86	.31	.25	.70			3000
<b>PN14-14R-3K</b>				1/4"	1.06	.44	.38	.83			3000
<b>PN10-6R-2K</b>	12-10 .04 Stock	Yellow	.225	#6	1.04	.38	.31	.86	CD9-3B	CD-800-3	2000
<b>PN10-8R-2K</b>				#8	1.04	.38	.31	.86			2000
<b>PN10-10R-2K</b>				#10	1.04	.38	.31	.86			2000
<b>PN10-14R-2K</b>				1/4"	1.19	.52	.38	.93			2000
<b>PN10-56R-2K</b>				5/16"	1.19	.52	.38	.93			2000
<b>PN10-38R-2K</b>				3/8"	1.27	.58	.43	.98			2000

Order number of pieces required, in multiples of standard reel quantity. *Prime items appear in BOLD.*

## HEAVY DUTY — Ring Terminals, Nylon Insulated

- Metal Insulation Grip Sleeve
- Heavy Stock



PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				CA9 Series Crimp Die	CA-800 Series Crimp Die	Pieces Per Reel
					A	W	C	G			
<b>PN12-6HDR-2K</b>	16-12 .05 Stock	Yellow	.225	#6	1.02	.31	.31	.86	CD9-3B	CD-800-3	2000
<b>PN12-8HDR-2K</b>				#8	1.02	.31	.31	.86			2000
<b>PN12-10HDR-2K</b>				#10	1.05	.38	.31	.86			2000
<b>PN12-14HDR-2K</b>				1/4"	1.20	.52	.38	.94			2000
<b>PN12-56HDR-2K</b>				5/16"	1.20	.52	.38	.94			2000
<b>PN12-38HDR-2K</b>				3/8"	1.28	.58	.38	.98			2000

Order number of pieces required, in multiples of standard reel quantity. *Prime items appear in BOLD.*

For Technical Assistance, call: 866-405-6659 (outside the U.S., see inside back cover for International Directory)

Reel Fed Ring Terminals — Nylon, TERMO and Heavy Duty