

LED



T3-1/4(9mm) MIN. CLUSTER BASE LEDs MINIATURE SCREW, MINIATURE WEDGE

FEATURES

DIRECTLY REPLACES STANDARD INCANDESCENTS

- LONG LIFE / 100,000 HOURS
- SOLID STATE, HIGH SHOCK/VIBRATION RESISTANT
- BUILT-IN CURRENT LIMITING RESISTOR FOR DIRECT APPLICATIONS FOR 5V to 240VAC
- CHOICE OF 8 COLORS
- LOW CURRENT, POWER SAVINGS to 100 - 500% AND MORE
- USED IN PILOT LIGHTS, INDUSTRIAL CONTROLS, LIGHTED PUSH BUTTON SWITCHES...

REPLACES FOLLOWING INCANDESCENTS

MIN. SCREW: 13, 14, 27, 31, 40, 41, 46, 48, 50, 52, 222, 223, 233, 245, 406, 407, 425, 428, 430, 432, 502, 605, 965, 1446, 1447, 1449, 1483, 1487, 1821, 1832...
MIN. WEDGE: 158, 159, 161, 168, 184, 192, 193, 194, 259, 280, 400, 555, 656, 657, 758...

PART NO.:

SN307 CR5 - 28V/20-P

MODEL #	LENS / COLOR / BRIGHT	VOLTS / mAmps Typ	POLARITY
CLUSTERS 6 - 7 LEDs T3-1/4(9mm) SCREW: SN306, SN307 = STD WEDGE: WN306, WN307 = STD	CR5K, CR3K, CR900, CR6, CR5, CR3, CO5, CY5, CY3, CLY5, CG5, CG3, CPG5, CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	SN306/WN306: 4V/90, 6V/160=EXT. RES. REQ'D SN307/WN307: 14V/40=EXT. RES. REQ'D SN306/WN306: 5V/90, 6V/90, 12V/60 SN307/WN307: 18V/30, 24V/30, 28V/30, 36V/30, 48V/20, 60V/20, 120VAC/10... Other Voltages / mAmps Available	CENTER CONTACT: P = ANODE (+) N = CATH. (-) P/NR = ANODE/ NO RESISTOR BP = BIPOLAR AC = VAC
MULTICHIP CLUSTERS T3-1/4(9mm) SCREW: SN324 = 24 CHIP WEDGE: WN324 = 24 CHIP	CR3K, CR7, CR6, CO6, CY6, CLY6, CG6, CPG6, CB6, CW6,	24V/50, 28V/50, 36V/30, 48V/30, 60V/15, 120VAC/15... Other Voltages / mAmps Available	CENTER CONTACT: P = ANODE (+) N = CATH. (-) P/NR = ANODE/ NO RESISTOR BP = BIPOLAR AC = VAC

**SPECIALS: BICOLORS, BLINKING, INFRAREDS;
RIGHT-ANGLE ILLUMINATORS...**


LENS TYPE: C=CLEAR,
COLOR CODES: R=RED, O=ORANGE, Y=AMBER YELLOW, LY=LIME YELLOW, G=GREEN,
PG=PURE GREEN, B=BLUE, W=WHITE (RED/GREEN)

BRIGHTNESS CODES: 900 = 900mcd WIDE RED, 3K = 3Kmcd NARROW RED, 5K = 5Kmcd NARROW RED,
7 = HI ULTRA RED ONLY, 6 = ULTRA, 5 = SUPER BRIGHT, 3/4 = HI EFFICIENCY


NOTE: WHEN PLACING ORDERS OR REQUESTING SAMPLES, PLEASE INDICATE INCANDESCENT LAMP NUMBER BEING REPLACED. WHEN SELECTING THE LED COLOR, MATCH EXISTING LENS COLOR TO LED COLOR.




SN306, SN307




WN306, WN307



SN324




WN324



SPECIALS

SN308, SN309



WN308, WN309

