

■ LOW POWER DISSIPATION STATIC RAMs (CONTINUED)

Memory capacity	Memory Configuration	Function mode	Max. access time (ns)	Type No.	Package Outline
1M	128Kx8	with (S1, S2, OE) I_{CC} (Power down) = 10 μ A (max) = 0.3 μ A (typ)	55	M5M51008BP-55LL	32P4
				M5M51008BFP-55LL	32P2M-A
				M5M51008BVP-55LL	32P3H-E
				M5M51008BRV-55LL	32P3H-F
				M5M51008BKR-55LL	★ 32P3K-B
				M5M51008BKR-55LL	★ 32P3K-C
			70	M5M51008BP-70LL	32P4
				M5M51008BFP-70LL	32P2M-A
				M5M51008BVP-70LL	32P3H-E
				M5M51008BRV-70LL	32P3H-F
				M5M51008BKR-70LL	★ 32P3K-B
				M5M51008BKR-70LL	★ 32P3K-C
			100	M5M51008BP-10LL	32P4
				M5M51008BFP-10LL	32P2M-A
				M5M51008BVP-10LL	32P3H-E
				M5M51008BRV-10LL	32P3H-F
				M5M51008BKR-10LL	★ 32P3K-B
				M5M51008BKR-10LL	★ 32P3K-C
	64Kx16	with (CS, BC1, BC2) I_{CC} (Power down) = 50 μ A (max) = 0.3 μ A (typ)	55	M5M51016BTP-55L	44P3W-H
				M5M51016BRT-55L	44P3W-L
				M5M51016BVP-55L	★★ 40P3J-A
				M5M51016BRV-55L	★★ 40P3J-B
			70	M5M51016BTP-70L	44P3W-H
				M5M51016BRT-70L	44P3W-L
				M5M51016BVP-70L	★★ 40P3J-A
				M5M51016BRV-70L	★★ 40P3J-B
			100	M5M51016BTP-10L	44P3W-H
				M5M51016BRT-10L	44P3W-L
				M5M51016BVP-10L	★★ 40P3J-A
				M5M51016BRV-10L	★★ 40P3J-B
		with (CS, BC1, BC2) I_{CC} (Power down) = 10 μ A (max) = 0.3 μ A (typ)	55	M5M51016BTP-55LL	44P3W-H
				M5M51016BRT-55LL	44P3W-L
				M5M51016BVP-55LL	★★ 40P3J-A
				M5M51016BRV-55LL	★★ 40P3J-B
			70	M5M51016BTP-70LL	44P3W-H
				M5M51016BRT-70LL	44P3W-L
				M5M51016BVP-70LL	★★ 40P3J-A
				M5M51016BRV-70LL	★★ 40P3J-B
			100	M5M51016BTP-10LL	44P3W-H
				M5M51016BRT-10LL	44P3W-L
				M5M51016BVP-10LL	★★ 40P3J-A
				M5M51016BRV-10LL	★★ 40P3J-B
2M	256Kx8	with (S1, S2, OE) I_{CC} (Power down) = 50 μ A (max) = 0.3 μ A (typ)	55	M5M5208FP-55L	★★ 32P2M-A
				M5M5208VP-55L	★★ 32P3H-E
				M5M5208RV-55L	★★ 32P3H-F
				M5M5208KV-55L	★★ 32P3K-B
				M5M5208KR-55L	★★ 32P3K-C
			70	M5M5208FP-70L	★★ 32P2M-A
				M5M5208VP-70L	★★ 32P3H-E
				M5M5208RV-70L	★★ 32P3H-F
				M5M5208KV-70L	★★ 32P3K-B
				M5M5208KR-70L	★★ 32P3K-C
			100	M5M5208FP-10L	★★ 32P2M-A
				M5M5208VP-10L	★★ 32P3H-E
				M5M5208RV-10L	★★ 32P3H-F
				M5M5208KV-10L	★★ 32P3K-B
				M5M5208KR-10L	★★ 32P3K-C

* The product listed above includes models which can support workpieces having a wide range of operating temperatures (-20 to 70°C/-40 to 85°C). Please contact our Sales Division whenever you need.