


NOTES:
 1. SPECIFICATIONS:
 ELECTRICAL:
 WITHSTANDING VOLTAGE: MINIMUM 1000 V RMS @ SEA LEVEL
 INSULATION RESISTANCE: INITIAL 5000 MEGOHMS MAXIMUM,
 1000 MEGOHMS MIN. AFTER ENVIRONMENTAL TESTING.
 CONTACT RATING: 5 AMPS
 CONTACT RESISTANCE: 2.7 MILLIOHMS MAX.
 MATERIALS:
 INSULATOR: BLACK UL94V-0 RATED GLASS FILLED NYLON
 CONTACT(030-1952-000): COPPER ALLOY
 CONTACT AREA PLATING: GOLD OVER NICKEL,
 CONNECTOR SHELL: STEEL, PLATING ZINC WITH CLEAR CHROMATE.
 ENVIRONMENTAL:
 OPERATING TEMPERATURE: -65°C TO +125°C
 TERMINATION:
 CRIMP WILL ACCOMODATE # 20 TO 28 AWG WIRE.
 TERMINATION-TOOLS:
 CRIMP TOOL: M22520/2-01
 INSERTION/EXTRACTION TOOL: CIET-20-HDB
 POSITIONER: EP-580
 2. DIMENSIONS IN [] ARE IN MILLIMETERS.


DRAWING REVISIONS			
REV	DOCUMENT	APP	DATE
A	DO 05-11146	AKB	01/07/06
B	ECN 06E296		

NUMBER OF POSITIONS	SELECTIVE GOLD FLASH PLATING (.120" [3.05] MTG. HOLES)		CONTACTS	DIMENSION									FRONT MOUNTING HOLE DIMENSIONS		REAR MOUNTING HOLE DIMENSIONS						
	PART NO.	FACTORY NO.		"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"	"J"	"K"	"X"	"Y"	"X"	"Y"				
9	DEUH-9P	702 03 09 001	INCLUDED	1.213 [30.81]	.984 [24.99]	.697 [17.70]	.360 [9.14]		.759 [19.28]									.874 [22.20]	.806 [20.47]		
	DEUH-9P-FO	702 03 09 005	NOT INCLUDED																		
15	DAUH-15P	702 03 15 001	INCLUDED	1.541 [39.14]	1.312 [33.32]	1.025 [26.03]	.494 [12.55]		1.083 [27.51]	.422 [10.72]								.513 [13.03]	1.134 [28.80]	.449 [11.40]	
	DAUH-15P-FO	702 03 15 005	NOT INCLUDED																		
25	DBUH-25P	702 03 25 001	INCLUDED	2.088 [53.04]	1.852 [47.04]	1.583 [40.21]	.378 [9.60]		1.629 [41.38]	.422 [10.72]									1.674 [42.52]		
	DBUH-25P-FO	702 03 25 005	NOT INCLUDED																		
37	DCUH-37P	702 03 37 001	INCLUDED	2.729 [69.32]	2.500 [64.50]	2.231 [56.67]	.484 [12.29]	.605 [15.37]	2.272 [57.71]	.534 [13.56]										2.326 [59.08]	
	DCUH-37P-FO	702 03 37 005	NOT INCLUDED																		
50	DDUH-50P	702 03 50 001	INCLUDED	2.635 [66.93]	2.406 [61.11]	2.127 [54.02]	.484 [12.29]	.605 [15.37]	2.178 [55.32]	.534 [13.56]										2.218 [56.34]	.555 [14.10]
	DDUH-50P-FO	702 03 50 005	NOT INCLUDED																		



RECOMENDED MTG. HOLE LAYOUT
 SEE CHART FOR FRONT AND REAR MTG. DIMENSIONS

ROHS COMPLIANT



UNITS	ENGLISH	PRO/E	MODELED BY: V. SKUZA
DO NOT SCALE DRAWING	DRAWN BY: V. SKUZA	DATE: 06/17/05	TITLE: D*U SERIES CRIMP & POKE CONNECTOR PLUG ASS'Y (.120" HOLES)
	DESIGN ENGINEER: A. BALI	06/17/05	MATERIAL: CONTROL SPEC NUMBER
	DESIGN ENGINEERING MGR.: A. SHAH	07/09/05	MATERIAL SPEC NUMBER FINISH PROJECT NUMBER: C14740
	MFG. ENGINEERING: J. OCEGUERA	07/07/05	CAD FILE NUMBER: DXUHXXP DRAWING NUMBER: D*UH-XXP
	QUALITY ASSURANCE: A. VAZQUEZ	07/06/05	CAGE IDENT NO. / SCALE: 71785 / B 1:1 SHEET 1 OF 1