



Technical Data Sheet

Side Face Silicon Phototransistor

PT2559B/L2-F

Features

- Fast response time
- High photo sensitivity
- Pb free
- This product itself will remain within RoHS compliant version.



Descriptions

- PT2559B/L2-F is a high speed and high sensitive dual phototransistor molded in a black plastic package with plat side view.
- The device is spectrally matched with IR emitters.


Applications

- Mouse
- Optoelectronic Switch
- Photo Interrupter

Device Selection Guide

| LED Part No. | Chip | Lens Color |
|--------------|----------|------------|
| | Material | |
| PT2559B/L2-F | Silicon | Black |

Package Dimensions



- Notes:** 1.All dimensions are in millimeters
 2.Tolerances unless dimensions ±0.25mm

Absolute Maximum Ratings (Ta=25°C)

| Parameter | Symbol | Rating | Units |
|-----------------------------------------------------------|------------------|-------------|-------|
| Collector-Emitter Voltage | V _{CEO} | 30 | V |
| Emitter-Collector-Voltage | V _{ECO} | 5 | V |
| Collector Current | I _C | 20 | mA |
| Operating Temperature | T _{opr} | -25 ~ +85°C | °C |
| Storage Temperature | T _{stg} | -40 ~ +85°C | °C |
| Lead Soldering Temperature(*1) | T _{sol} | 260 | °C |
| Power Dissipation at (or below) 25°C Free Air Temperature | P _D | 75 | mW |

Notes: *1:Soldering time ≤ 5 seconds.

Electro-Optical Characteristics (Ta=25°C)

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|---------------------------------------|-----------------|------------------------------------------------|-----|-----|------|---------|
| Collector – Emitter Breakdown Voltage | BV_{CEO} | $I_C=100\ \mu A$ $E_e=0mW/cm^2$ | 30 | --- | --- | V |
| Emitter-Collector Breakdown Voltage | BV_{ECO} | $I_E=100\ \mu A$ $E_e=0mW/cm^2$ | 5 | --- | --- | V |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_C=2mA$ $E_e=1mW/cm^2$ | --- | --- | 0.4 | V |
| Rise Time | t_r | $V_{CE}=5V$ $I_C=1mA$ $R_L=1000\ \Omega$ | --- | 15 | --- | μS |
| Fall Time | t_f | | --- | 15 | --- | |
| Collector Dark Current | I_{CEO} | $E_e=0mW/cm^2$ $V_{CE}=20V$ | --- | --- | 100 | nA |
| On State Collector Current | $I_{C(on)}$ | $V_{CE}=5V,$ $E_e=0.555mW/cm^2$ | 129 | --- | 1085 | μA |
| Wavelength of Peak Sensitivity | λ_p | --- | --- | 940 | --- | nm |
| Rang of Spectral Bandwidth | $\lambda_{0.5}$ | --- | 760 | --- | 1100 | nm |

Typical Electro-Optical Characteristics Curves

Fig.1 Power Dissipation vs. Ambient Temperature




Fig.2 Spectral Sensitivity




Fig.3 Dark Current vs. Ambient Temperature





Fig. 4 Reverse Light Current vs. E_e



Typical Electro-Optical Characteristics Curves

Fig.5 Terminal Capacitance vs. Reverse Voltage





Fig.6 Response Time vs. Load Resistance




Test Method For On State Collector Current :

Condition : $E_e=0.555\text{mW/cm}^2$, $V_{CE}=5\text{V}$

Test Item : Collector Current [$I_{C(on)}$]

Unit : μA



To Distinguish Intensity:

Condition: $V_{CE}:5\text{V}$ $E_e:0.555\text{mW/cm}^2$

A Ranks

| Color Code | Ranks | Symbol | Min | Typ | Max | Unit | Test Condition |
|------------|-------|-------------|-----|-----|------|---------------|-----------------------------------------------|
| Red | A1 | $I_{C(ON)}$ | 129 | --- | 226 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Blue | A2 | $I_{C(ON)}$ | 195 | --- | 306 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Yellow | A3 | $I_{C(ON)}$ | 262 | --- | 380 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Silver | A4 | $I_{C(ON)}$ | 330 | --- | 461 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Green | A5 | $I_{C(ON)}$ | 398 | --- | 544 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Purple | A6 | $I_{C(ON)}$ | 468 | --- | 625 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| White | A7 | $I_{C(ON)}$ | 536 | --- | 703 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Brown | A8 | $I_{C(ON)}$ | 604 | --- | 785 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Orange | A9 | $I_{C(ON)}$ | 673 | --- | 862 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Golden | A10 | $I_{C(ON)}$ | 742 | --- | 944 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Pink | A11 | $I_{C(ON)}$ | 812 | --- | 1018 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |
| Red,Blue | A12 | $I_{C(ON)}$ | 882 | --- | 1085 | μA | $E_e=0.555\text{mW/c m}^2$ $V_{CE}=5\text{V}$ |

* $I_{C(ON)}=[I_{C(ON)A}+ I_{C(ON)B}]/2$



Packing Quantity Specification

- 1. 1000Pcs/1Bag , 8Bags/1Box
- 2. 10Boxes/1Carton



CPN:

P/N:



PT2559B/L2-F

QTY:



LOT NO:



CAT:

HUE:

REF:

Label Form Specification

CPN: Customer's Production Number

P/N : Production Number

QTY: Packing Quantity

CAT: Ranks

HUE: Peak Wavelength

REF: Reference

LOT No: Lot Number

Notes

- 1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
- 2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
- 3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.

EVERLIGHT ELECTRONICS CO., LTD.

Office: No 25, Lane 76, Sec 3, Chung Yang Rd,
Tucheng, Taipei 236, Taiwan, R.O.C

Tel: 886-2-2267-2000, 2267-9936

Fax: 886-2267-6244, 2267-6189, 2267-6306

<http://www.everlight.com>