



SFAF801G - SFAF808G

Isolated 8.0 AMPS.

Glass Passivated Super Fast Rectifiers


ITO-220AC

Features

- ◇ UL Recognized File # E-326243
- ◇ High efficiency, low VF
- ◇ High current capability
- ◇ High reliability
- ◇ High surge current capability
- ◇ Low power loss.
- ◇ For use in low voltage, high frequency inverter, free wheeling, and polarity protection application
- ◇ Green compound with suffix "G" on packing code & prefix "G" on datecode.


Mechanical Data

- ◇ Cases: ITO-220AC molded plastic
- ◇ Epoxy: UL 94V-0 rate flame retardant
- ◇ Terminals: Pure tin plated, lead free. solderable per MIL-STD-202, Method 208 guaranteed
- ◇ Polarity: As marked
- ◇ High temperature soldering guaranteed: 260°C/10 seconds 0.25", (6.35mm) from case.
- ◇ Weight: 1.7 grams
- ◇ Mounting torque: 5 in – 1bs. max.



Dimensions in inches and (millimeters)

Marking Diagram



SFAF80XG = Specific Device Code
 G = Green Compound
 Y = Year
 WW = Work Week

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

| Type Number | Symbol | SFAF 801G | SFAF 802G | SFAF 803G | SFAF 804G | SFAF 805G | SFAF 806G | SFAF 807G | SFAF 808G | Units |
|--|--------------------|-------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|----------|
| Maximum Recurrent Peak Reverse Voltage | VRRM | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 | V |
| Maximum RMS Voltage | VRMS | 35 | 70 | 105 | 140 | 210 | 280 | 350 | 420 | V |
| Maximum DC Blocking Voltage | VDC | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 | V |
| Maximum Average Forward Rectified Current @T _c = 100 °C | I _{F(AV)} | 8.0 | | | | | | | | A |
| Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method) | I _{FSM} | 125 | | | | | | | | A |
| Maximum Instantaneous Forward Voltage @ 8.0A | V _F | 0.95 | | 1.3 | | 1.7 | | | | V |
| Maximum DC Reverse Current @T _A =25 °C at Rated DC Blocking Voltage @ T _A =100 °C (Note 1) | I _R | 10 | | | | 400 | | | | uA uA |
| Maximum Reverse Recovery Time (Note 4) | T _{rr} | 35 | | | | | | | | nS |
| Typical Junction Capacitance (Note 2) | C _j | 90 | | | | 60 | | | | pF |
| Typical Thermal Resistance (Note 3) | R _{θJC} | 4.0 | | | | | | | | °C/W |
| Operating Temperature Range | T _J | -65 to +150 | | | | | | | | °C |
| Storage Temperature Range | T _{STG} | -65 to +150 | | | | | | | | °C |

- Notes: 1. Pulse Test with PW=300 usec, 1% Duty Cycle
 2. Measured at 1 MHz and Applied Reverse Voltage of 4.0 V D.C.
 3. Mounted on Heatsink Size of 2" x 3" x 0.25" Al-Plate..
 4. Reverse Recovery Test Conditions: I_F=0.5A, I_R=1.0A, I_{RR}=0.25A

RATINGS AND CHARACTERISTIC CURVES (SFAF801G THRU SFAF808G)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- TYPICAL REVERSE CHARACTERISTICS




FIG.3- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE





FIG.6- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



NOTES: 1. Rise Time=7ns max. Input Impedance= 1 megohm 22pf
2. Rise Time=10ns max. Source Impedance= 50 ohms

