


# 8A10F-8A100F

Plastic Silicon Rectifiers

**VOLTAGE RANGE: 100 --- 1000 V**

**CURRENT: 8.0 A**




## ITO-220AC

### Features

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

### Mechanical Data

- ◇ Case: JEDEC ITO-220AC, molded plastic
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.056 ounces, 1.587 grams
- ◇ Mounting position: Any



Dimensions in millimeters

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.


		8A10F	8A20F	8A40F	8A60F	8A80F	8A100F	UNITS
Maximum recurrent peak reverse voltage	$V_{RRM}$	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	70	140	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	100	200	400	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ C$	$I_{F(AV)}$	8.0						A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ C$	$I_{FSM}$	400						A
Maximum instantaneous forward voltage @ 8.0 A	$V_F$	1.0						V
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	$I_R$	10 100						$\mu A$
Typical junction capacitance (Note1)	$C_J$	120						pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	10						$^\circ C/W$
Operating junction temperature range	$T_J$	- 55 ---- + 150						$^\circ C$
Storage temperature range	$T_{STG}$	- 55 ---- + 150						$^\circ C$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


2. Thermal resistance from junction to ambient.

## Ratings AND Characteristic Curves


**FIG.1 – FORWARD DERATING CURVE**



**FIG.2 – TYPICAL FORWARD CHARACTERISTICS**



**FIG.3 – MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**



**FIG.4 – TYPICAL JUNCTION CAPACITANCE**

