



Features


- ◇ For IF SAW filter
- ◇ High attenuation
- ◇ Single-ended operation
- ◇ Dual In-line Package
- ◇ RoHS compliant (2002/95/EC), Pb-free

Specifications


Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	66	66.1	66.2
Insertion Loss	dB	-	26.5	28
1 dB Bandwidth	MHz	3	3.06	-
40 dB Bandwidth	MHz	-	4.27	4.4
50 dB Bandwidth	MHz	-	4.35	4.5
Passband Variation	dB	-	0.6	1
Phase Linearity	deg	-	5	6.4
Absolute Delay	usec	-	2.76	4
Ultimate Rejection	dB	45	47	-
Material Temperature coefficient	KHz/°C	0.066		
Substrate Material	-	Qz		
Ambient Temperature	°C	25		
Operating Temperature Range	°C	-40	-	+85
Storage Temperature Range	°C	-45	-	+105
DC Voltage	V	0		
Input Power	dBm	-	-	10
ESD Class	-	1C		
Package Size	DIP2712 (27.0x12.8x4.7mm3)			

Notes:

1. All specifications are based on the test circuit shown;
2. In production, all specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature;
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances;
4. This is the optimum impedance in order to achieve the performance show.

	SIPAT Co., Ltd. (CETC No.26 Research Institute) #14 Nanping Huayuan Road, Chongqing, China, 400060	Part Number	LBS06608	
		Rev. Date	2009-07-31	
		Ver.	1.0	Page 1/3

Matching Configuration




$$L1 = (480 + 82) \text{ nH} \quad L2 = 470 \text{ nH}$$

$$C1 = 27 \text{ pF}$$

Source/Load Impedance = 50 ohm

Notes - Component values may change depending on board layout.

Package Dimension



Pad Configuration:

Input 1
Output 5
Ground All Others

Marking Configuration:

- 1) SIPAT: Manufacturer Name
- 2) LBS06608: Part Number
- 3) XXYY: Date (Year/month)
- 4) ZZ: Identified Code

Package: DIP2712

Unit: mm




SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number	LBS06608	
Rev. Date	2009-07-31	
Ver.	1.0	Page 2/3

Typical Performance


Frequency Respond



Horizontal: 2MHz/Div

Vertical: 10dB/Div


Passband Respond



Horizontal: 1MHz/Div

Vertical: 0.5dB/Div


Group Delay Variation($f_0 \pm 1.5\text{MHz}$)



Horizontal: 1MHz/Div

Vertical: 200ns/Div


Phase Linearity($f_0 \pm 1.5\text{MHz}$)




Horizontal: 1MHz/Div

Vertical: 5deg/Div

Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number

LBS06608

Rev. Date

2009-07-31

Ver.

1.0

Page 3/3