



Frontier Electronics Corp.

667 E. COCHRAN STREET, SIMI VALLEY, CA 93065

TEL: (805) 522-9998 FAX: (805) 522-9989

E-mail: frontiersales@frontierusa.com

Web: <http://www.frontierusa.com>

8A CENTER TAP RECTIFIERS


BCT8-005-LFR THRU BCT8-10-LFR

FEATURES

- PLASTIC MATERIAL HAS UNDERWRITERS LABORATORY FLAMMABILITY CLASSIFICATION 94V-0
- HIGH TEMPERATURE SOLDERING GUARANTEED: 260°C /10 S 0.375" (9.5mm) LEAD LENGTH AT 5 LBS (2.3KG) TENSION
- LEAD FREE

MECHANICAL DATA

- CASE: ALUMINUM HEAT SINK CASE, DIMENSIONS IN INCHES MILLIMETERS
- TERMINALS: SOLDERABLE PER MIL-STD-202, METHOD 208
- MOUNTING POSITION: ANY
- WEIGHT: 15.0 GRAMS



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD. FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%

RATINGS	SYMBOL	BCT8 -005-LFR	BCT 8 -01-LFR	BCT 8 -02-LFR	BCT 8 -04-LFR	BCT 8 -06-LFR	BCT 8 -08-LFR	BCT 8 -10-LFR	UNITS
MAXIMUM RECURRENT PEAK REVERSE VOLTAGE	V_{RRM}	50	100	200	400	600	800	1000	V
MAXIMUM RMS VOLTAGE	V_{RMS}	35	70	140	280	420	560	700	V
MAXIMUM DC BLOCKING VOLTAGE	V_{DC}	50	100	200	400	600	800	1000	V
MAXIMUM AVERAGE FORWARD RECTIFIED OUTPUT CURRENT (SEE FIG.1)	I_O	8.0							A
PEAK FORWARD SURGE CURRENT SINGLE SINE-WAVE SUPERIMPOSED ON RATED LOAD	I_{FSM}	300							A
STORAGE TEMPERATURE RANGE	T_{STG}	- 55 TO + 150							°C
OPERATING TEMPERATURE RANGE	T_{OP}	- 55 TO + 150							°C

ELECTRICAL CHARACTERISTICS ($A_T T_A = 25^\circ C$ UNLESS OTHERWISE NOTED)

CHARACTERISTICS	SYMBOL	BCT8 -005-LFR	BCT 8 -01-LFR	BCT 8 -02-LFR	BCT 8 -04-LFR	BCT 8 -06-LFR	BCT 8 -08-LFR	BCT 8 -10-LFR	UNITS
MAXIMUM INSTANTANEOUS FORWARD VOLTAGE DROP PER ELEMENT AT 10Amp	V_F	1.0							V
MAXIMUM REVERSE LEAKAGE AT RATED DC BLOCKING VOLTAGE PER ELEMENT $T_A = 25^\circ C$	I_R	10							μA

RATINGS AND CHARACTERISTIC CURVES BCT8-005-LFR THRU BCT8-10-LFR

FIG. 1 - DERATING CURVE OUTPUT RECTIFIED CURRENT





FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



TEMPERATURE, (°C)

FIG. 3 - TYPICAL JUNCTION CAPACITANCE PER ELEMENT




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER ELEMENT

