




X1049A

NPN SILICON TRANSISTOR

HIGH GAIN TRANSISTOR

■ FEATURES

- * $V_{CEV} = 80V$
- * High Gain
- * 20 Amps pulse current



TO-92

■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
X1049AL-T92-B	X1049AG-T92-B	TO-92	E	B	C	Tape Box
X1049AL-T92-K	X1049AG-T92-K	TO-92	E	B	C	Bulk
X1049AL-T92-R	X1049AG-T92-R	TO-92	E	B	C	Tape Reel

X1049AL-T92-B (1) Packing Type (2) Package Type (3) Lead Free	(1) B: Tape Box, K: Bulk, R: Tape Reel (2) T92: TO-92 (3) G: Halogen Free, L: Lead Free
---	--

■ ABSOLUTE MAXIMUM RATING (T_A=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	V _{CBO}	80	V
Collector-Emitter Voltage	V _{CEO}	25	V
Emitter-Base Voltage	V _{EBO}	5	V
Collector Current	I _C	4	A
		20	A
Base Current	I _B	500	mA
Power Dissipation	P _D	1	W
Junction Temperature	T _J	125	°C
Operating Temperature	T _{OPR}	-20 ~ +85	°C
Storage Temperature	T _{STG}	-40 ~ +150	°C







Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise specified)



PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	V _{CBO}	I _C =100μA	80	120		V
Collector-Emitter Breakdown Voltage	V _{CEO}	I _C =10mA	25	35		V
Collector-Emitter Breakdown Voltage	V _{CES}	I _C =100μA	80	120		V
Collector-Emitter Breakdown Voltage	V _{CEV}	I _C =100μA, V _{EB} =1V	80	120		V
Emitter-Base Breakdown Voltage	V _{EBO}	I _E =100μA	5	8.75		V
Collector Cut-Off Current	I _{CBO}	V _{CB} =50V		0.3	10	nA
Emitter Cut-Off Current	I _{EBO}	V _{EB} =4V		0.3	10	nA
Collector Emitter Cut-Off Current	I _{CES}	V _{CES} =50V		0.3	10	nA
Collector-Emitter Saturation Voltage (Note)	V _{CE(SAT)}	I _C =0.5A, I _B =10mA		30	70	mV
		I _C =1A, I _B =10mA		60	130	
		I _C =2A, I _B =10mA		125	280	
		I _C =4A, I _B =50mA		155	400	
Base-Emitter Saturation Voltage (Note)	V _{BE(SAT)}	I _C =4A, I _B =50mA		890	980	mV
Base-Emitter Turn-On Voltage (Note)	V _{BE(ON)}	I _C =4A, V _{CE} =2V		820	920	mV
DC Current Gain (Note)	h _{FE}	I _C =10mA, V _{CE} =2V	250	430		
		I _C =0.5A, V _{CE} =2V	300	450		
		I _C =1A, V _{CE} =2V	300	450	1200	
		I _C =4A, V _{CE} =2V	200	350		
		I _C =20A, V _{CE} =2V	7			
Transition Frequency	f _T	I _C =50mA, V _{CE} =10V, f=50MHz		180		MHz
Output Capacitance	C _{OBO}	V _{CB} =10V, f=1MHz		45	60	pF
Turn-On Time	t _{ON}	I _C =4A, I _B =40mA, V _{CC} =10V		125		ns
Turn-Off Time	t _{OFF}	I _C =4A, I _B =±40mA, V _{CC} =10V		380		ns

Note: Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤2%

■ TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.