

# Specialty Extension Cords and Lighting

9



Carol® Brand Specialty Extension Cord Products are uniquely designed for specific uses by contractors, do-it-yourselfers and homeowners alike.

The Shock Safe® 3-outlet Powr-Center® has a built-in ground fault circuit interrupter (GFCI) for detecting power leaks. Featuring weather-resistant test and reset buttons, the GFCI cuts off electricity to prevent electric shock.

Carol offers 3-outlet Powr-Centers® for use when multiple outlets are needed indoors. The three-conductor cords are designed specifically for household, office or workshop use.

Carol offers three-conductor standard Utility Lights with plastic or metal guards. Our Brooder Lamp and Clamp Lights are also available to meet your lighting needs.

| Index  | Page |
|--|------|
| Shock Safe® Ground Fault Circuit Interrupter (GFCI) Powr-Center® | 62   |
| Household Powr-Centers®  | 62   |
| Plastic Guard Utility Light                                      | 63   |
| Metal Guard Utility Light  | 63   |
| Brooder and Heat Lamp  | 64   |
| Clamp Light  | 64   |

# Shock Safe® Ground Fault Circuit Interrupter (GFCI) Powr-Center®

3 Conductor • Type SJTW • -40°C to 60°C • 300 Volts

### POWR-CENTER® WITH 3 OUTLETS

| CATALOG NUMBER | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING |      |       | PKG. PER CTN. | WT./ UNIT LBS | WT./ CTN. LBS | UPC CODE     |
|----------------|--------------|----------|---------------------|-----------------|--------------|------|-------|---------------|---------------|---------------|--------------|
|                |              |          |                     |                 | VOLTS        | AMPS | WATTS |               |               |               |              |
| 04000.63.05    | 3            | 12       | 2                   | Yellow          | 125          | 15   | 1875  | 6             | 1.3           | 8             | 079407040001 |



**Product Description:**

The Shock Safe® 3-outlet Powr-Center® has a built-in GFCI for detecting power leaks. Featuring weather-resistant test and reset buttons, the GFCI cuts off electricity to prevent electric shock.

**Product Construction:**

**Conductor:**

- 12 AWG stranded bare copper per ASTM B-174

**Insulation:**

- Premium-grade, color-coded PVC

**Jacket:**

- PVC; yellow
- Temperature range: -40°C to 60°C
- Voltage rating: 300 volts

**Applications:**

- Power tools
- Appliances

**Features:**

- Integral GFCI detects power leaks and cuts off electricity to prevent electric shock
- Test and reset buttons
- 3-conductor grounded

**Industry Approvals:**

- UL Listed
- OSHA Acceptable

# Household Powr-Centers®

3-Conductor Grounded • Type SPT-3 and SJT • 60°C • 300 Volts

| CATALOG NUMBER    | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING |      |       | PKG. PER CTN. | WT./ UNIT LBS | WT./ CTN. LBS | UPC CODE     |
|-------------------|--------------|----------|---------------------|-----------------|--------------|------|-------|---------------|---------------|---------------|--------------|
|                   |              |          |                     |                 | VOLTS        | AMPS | WATTS |               |               |               |              |
| <b>TYPE SPT-3</b> |              |          |                     |                 |              |      |       |               |               |               |              |
| 00655.63.04       | 3            | 14       | 3                   | Orange          | 125          | 15   | 1875  | 10            | 0.6           | 6             | 079407006557 |
| <b>TYPE SJT</b>   |              |          |                     |                 |              |      |       |               |               |               |              |
| 00565.63.17       | 3            | 16       | 9                   | Beige           | 125          | 13   | 1625  | 12            | 0.7           | 8             | 079407005659 |



**Product Construction:**

**Conductor:**

- 16 AWG or 14 AWG stranded bare copper per ASTM B-174

**Insulation:**

- Premium-grade, color-coded PVC

**Jacket:**

- PVC; orange or beige
- Voltage rating: 300 volts

**Applications:**

- Clocks
- Lamps
- Holiday lighting
- Other household appliances

**Features:**

- 3 grounded outlets

**Industry Approvals:**

- UL Listed

