


# SBC



## EB-381LF

VIA Mark Mini Board w /  
VGA / Audio / LAN

### Features :

- Support VIA Mark CPU up to 533MHz
- Equipped with Mark + VT82C686B with FSB 100/133MHz
- Memory Supports PC100/133 SDRAM up to 512MB
- Support Compact Flash
- Expansion Slots for PC104



No. 24, Lane 365, Yang Guang St., Nei Hu District, Taipei 114, Taiwan, R.O.C.

Tel: +886-2-8751-1111

Fax: +886-2-8751-1199

Email: [sales@protech.com.tw](mailto:sales@protech.com.tw)

<http://www.protech.com.tw>




ISO CERTIFIED

9001 14001

# EB-381LF

VIA Mark Mini Board w / VGA / Audio / LAN



## Specifications

<b>System</b>	
<b>CPU Type</b>	VIA Mark Processor
<b>CPU Frequency</b>	533/800MHz
<b>Chipset</b>	Mark + VT82C686B (FSB : 100/133MHz)
<b>DRAM</b>	1 x 144-pin SO-DIMM, support PC100/133 SDRAM up to 512MB
<b>BIOS</b>	Phoenix-Award PnP BIOS, with VGA BIOS
<b>Watchdog</b>	16 level Watchdog timer selectable w/Reset/NMI
<b>Power Supply</b>	Supports AT/ATX power
<b>Power Requirement</b>	+5V, +12V
<b>Power Consumption</b>	+5VSB : 0.78A / +5V : 3.32A / +12V : 1.52A (VIA Mark 533MHz)
<b>Dimension</b>	102mm x 145mm (4.02" x 5.71")

## I/O Chipset

<b>IDE Interface</b>	1 x 44-pin IDE
<b>CF</b>	1 x compact flash slot (IDE)
<b>FDD Interface</b>	1
<b>Bus Interface</b>	PC/104
<b>Serial Port</b>	2 x COM ports, COM1 for RS232, COM2 for RS232/422/485 (for 16550 compatible type of UART)
<b>Parallel Port</b>	1 x parallel (SPP / EPP / ECP)
<b>IrDA</b>	1 (SIR)

<b>Keyboard</b>	Mini DIN connector or Y-cable
<b>Mouse</b>	External connector or Mini Din connector with Y-cable
<b>LAN</b>	Realtek RTL8100BL (10/100Mbps) Support Wake-on-LAN with ATX power
<b>Audio</b>	AC '97 Codec, Realtek ALC202A with Line-in / Line-out / MIC
<b>USB</b>	4 x USB 1.1

## Display

<b>Graphic</b>	Built-in VIA Mark, share system memory, Support CRT & LVDS, TV-OUT
<b>LCD Interface</b>	18/36-bit LVDS

## Environment

<b>OperationTemp.</b>	0°~60°C(32°~140°F)
<b>Storage Temp.</b>	-40°~85°C(-40°~185°F)
<b>Humidity</b>	Operation humidity 20~90%, Storage humidity 20~95%

## Ordering Information

<b>EB-381LF-C533</b>	3.5" SBC w VIA Mark 533MHz / VGA / Audio / TV / LAN
<b>EB-381LF-C800</b>	3.5" SBC w VIA Mark 800MHz / VGA / Audio / TV / LAN
<b>Certificate: CE, FCC, CLASS A</b>	

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in MAY. 2007.