

### IGBT MODULE (S series) 1400V / 15A / PIM



#### ■ Features

#### ■ Applications

- Inverter for Motoe Drive
- AC and DC Servo Drive Amplifier
- Uninterruptible Power Supply

#### ■ Maximum ratings and characteristics

● Absolute maximum ratings (Tc=25°C unless without specified)

Item	Symbol	Condition	Rating	Unit		
Inverter	Collector-Emitter voltage	V <sub>CES</sub>	1400	V		
	Gate-Emitter voltage	V <sub>GES</sub>	±20	V		
	Collector current	I <sub>C</sub>	Continuous	T <sub>c</sub> =25°C	25	A
				T <sub>c</sub> =75°C	15	
		I <sub>CP</sub>	1ms	T <sub>c</sub> =25°C	50	A
				T <sub>c</sub> =75°C	30	
-I <sub>C</sub>			15	A		
Collector power dissipation	P <sub>C</sub>	1 device	110	W		
Brake	Collector-Emitter voltage	V <sub>CES</sub>	1400	V		
	Gate-Emitter voltage	V <sub>GES</sub>	±20	V		
	Collector current	I <sub>C</sub>	Continuous	T <sub>c</sub> =25°C	25	A
				T <sub>c</sub> =75°C	15	
		I <sub>CP</sub>	1ms	T <sub>c</sub> =25°C	50	A
				T <sub>c</sub> =75°C	30	
Collector power dissipation	P <sub>C</sub>	1 device	110	W		
Repetitive peak reverse voltage	V <sub>R</sub> RM		1400	V		
Converter	Repetitive peak reverse voltage	V <sub>R</sub> RM	1600	V		
	Average output current	I <sub>O</sub>	50Hz/60Hz sine wave	15	A	
	Surge current (Non-Repetitive)	I <sub>FSM</sub>	T <sub>j</sub> =150°C, 10ms	155	A	
	I <sup>2</sup> t (Non-Repetitive)	I <sup>2</sup> t	half sine wave	120	A <sup>2</sup> s	
Operating junction temperature	T <sub>j</sub>		+150	°C		
Storage temperature	T <sub>stg</sub>		-40 to +125	°C		
Isolation voltage	between terminal and copper base *2	V <sub>iso</sub>	AC : 1 minute	AC 2500	V	
	between thermistor and others *3			AC 2500		
Mounting screw torque			3.5 *1	N·m		

\*1 Recommendable value : 2.5 to 3.5 N·m (M5)

\*2 All terminals should be connected together when isolation test will be done.

\*3 Terminal 8 and 9 should be connected together. Terminal 1 to 7 and 10 to 24 should be connected together and shorted to copper base.

## ● Electrical characteristics (T<sub>j</sub>=25°C unless otherwise specified)


Item	Symbol	Condition	Characteristics			Unit		
			Min.	Typ.	Max.			
Inverter	Zero gate voltage collector current	ICES	V <sub>CE</sub> =1400V, V <sub>GE</sub> =0V		1.0	mA		
	Gate-Emitter leakage current	IGES	V <sub>CE</sub> =0V, V <sub>GE</sub> =±20V		0.2	μA		
	Gate-Emitter threshold voltage	V <sub>GE(th)</sub>	V <sub>CE</sub> =20V, I <sub>c</sub> =15mA		5.5	7.2	8.5	V
	Collector-Emitter saturation voltage	V <sub>CE(sat)</sub>	V <sub>GE</sub> =15V, I <sub>c</sub> =15A	chip	2.2		V	
				terminal	2.25	2.7		
	Input capacitance	C <sub>ies</sub>	V <sub>GE</sub> =0V, V <sub>CE</sub> =10V, f=1MHz		1800		pF	
	Turn-on time	t <sub>on</sub>	V <sub>CC</sub> =800V I <sub>c</sub> =15A V <sub>GE</sub> =±15V		0.35	1.2	μs	
					0.25	0.6		
					0.1			
	Turn-off	t <sub>off</sub>	R <sub>G</sub> =82Ω		0.45	1.0		
				0.08	0.3			
Forward on voltage	V <sub>F</sub>	I <sub>F</sub> =15A	chip	2.4		V		
			terminal	2.45	3.3			
Reverse recovery time of FRD	t <sub>rr</sub>	I <sub>F</sub> =15A			0.35	μs		
Brake	Zero gate voltage collector current	ICES	V <sub>CEs</sub> =1400V, V <sub>GE</sub> =0V		1.0	mA		
	Gate-Emitter leakage current	IGES	V <sub>CE</sub> =0V, V <sub>GE</sub> =±20V		0.2	μA		
	Collector-Emitter saturation voltage	V <sub>CE(sat)</sub>	I <sub>c</sub> =15A, V <sub>GE</sub> =15V	chip	2.2		V	
				terminal	2.3	2.7		
	Turn-on time	t <sub>on</sub>	V <sub>CC</sub> =800V I <sub>c</sub> =15A V <sub>GE</sub> =±15V		0.35	1.2	μs	
					0.25	0.6		
	Turn-off time	t <sub>off</sub>	R <sub>G</sub> =82Ω		0.45	1.0		
					0.08	0.3		
	Reverse current	I <sub>RRM</sub>	V <sub>R</sub> =1400V			1.0	mA	
	Forward on voltage	V <sub>FM</sub>	I <sub>F</sub> =15A	chip	1.1		V	
terminal				1.2	1.5			
Resistance	R	T=25°C		5000		Ω		
		T=100°C	465	495	520			
B value	B	T=25/50°C	3305	3375	3450	K		

## ● Thermal resistance Characteristics







Item	Symbol	Condition	Characteristics			Unit
			Min.	Typ.	Max.	
Thermal resistance ( 1 device )	R <sub>th(j-c)</sub>	Inverter IGBT			1.14	°C/W
		Inverter FWD			1.85	
		Brake IGBT			1.14	
		Converter Diode			1.30	
Contact thermal resistance *	R <sub>th(c-f)</sub>	With thermal compound		0.05		







\* This is the value which is defined mounting on the additional cooling fin with thermal compound






## ■ Equivalent Circuit Schematic









■ Characteristics (Representative)










■ Outline Drawings, mm



mass : 180g