



**Material:**

- Conductor:
  - Bare Copper 24AWG 7/0.196±0.015MM
- Insulator:
  - Thickness Min. at any point: 0.15MM
  - Thickness Max. Avg.: 0.25MM
  - Diameter: 1.04±0.06MM
- Jacket PVC:
  - Thickness Min. at any point: 0.46MM
  - Thickness Max. Avg.: 0.58MM
  - Diameter: 5.9±0.15MM

orange 1 white/orange	green 2 white/green
blue 3 white/blue	brown 4 white/brown

PA/R	PINOUT		
	P1(T568B)	WIRE	P2(T568B)
1	1	WHT/ORG	1
	2	ORG	2
2	3	WHT/GRN	3
	6	GRN	6
3	4	BLU	4
	5	WHT/BLU	5
4	7	WHT/BRN	7
	8	BRN	8

Ⓜ = Assmann logo



ITEM NO.	<b>A-MCU60020-R</b>
TITLE	Cat.6 UTP Patch Cable - 8P8C 50μ", Grey, 2 Meters

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
©Copyright 2010 by Assmann Electronic Components  
All International Rights Reserved