



| | |
|--------------------------|------------------------|
| orange 1 white/orange | green 2 white/green |
| blue 3 white/blue | brown 4 white/brown |

Material:

- Conductor:
 - Bare Copper 24AWG 7/0.196±0.015MM
- Insulator:
 - Thickness Min. at any point: 0.15MM
 - Thickness Max. Avg.: 0.25MM
 - Diameter: 1.04±0.06MM
- Jacket PVC:
 - Thickness Min. at any point: 0.46MM
 - Thickness Max. Avg.: 0.58MM
 - Diameter: 5.9±0.15MM

| PA/R | PINOUT | | |
|------|-----------|---------|-----------|
| | P1(T568B) | WIRE | P2(T568B) |
| 1 | 1 | WHT/ORG | 1 |
| | 2 | ORG | 2 |
| 2 | 3 | WHT/GRN | 3 |
| | 6 | GRN | 6 |
| 3 | 4 | BLU | 4 |
| | 5 | WHT/BLU | 5 |
| 4 | 7 | WHT/BRN | 7 |
| | 8 | BRN | 8 |

Ⓜ = Assmann logo



ITEM NO.
A-MCU60070/Y-R
 TITLE
 Cat.6 UTP Patch Cable - 8P8C 50μ", Yellow, 7 Meters

ASSMANN
 Electronics, Inc.
 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
 Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
 ©Copyright 2010 by Assmann Electronic Components
 All International Rights Reserved