

**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

# MBRX120LSF

## **Features**

- High Surge Capability
- Super Low Forward Voltage Drop
- Low Profile Package
- Lead Free Finish/Rohs Compliant(Note1) ("P"Suffix designates Compliant. See ordering information)

## **Mechanical Data**

- Packaging:SOD-123FL
- Marking Code: L2
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1


### **Maximum Ratings**

-							
Symbol	Parameter	Rating	Unit				
VR(RMS)	Maximum RMS Voltage	14	V				
V <sub>RRM</sub>	Repetitive Reverse Voltage	20	V				
I <sub>F(AV)</sub>	Average Forward Current	1	A				
I <sub>FSM</sub>	Surge Forward Current at 8.3ms	50	А				
RthJL	Typical Thermal Resistance Junction to lead	26	°C/W				
TJ	Operating Junction Temperature	-65 to +125	°				
T <sub>STG</sub>	Storage Temperature	-65 to +125	°C				


## Low Forward Volatge Drop

### **Schottky Barrier**

Diodes



DIMENSIONS						
DIM	INCHES		MM		NOTE	
	MIN	MAX	MIN	MAX		
Α	.140	.152	3.55	3.85		
В	.100	.112	2.55	2.85		
С	.055	.071	1.40	1.80		
D	.037	.053	0.95	1.35		
Е	.020	.039	0.50	1.00		
G	.010		0.25			
Н		.008		.20		



### Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
V <sub>F</sub>	Forward Voltage @0.1A		0.34	
	@1A		0.45	V
	@3A		0.65	
I <sub>R</sub>	Leakage Current @VR=20V		0.4	mA

Note

1. Mounted with minimum recommended pad size, FR4 board.





# **MBRX120LSF**




Figure 1. Typical Forward Voltage

Figure 2. Typical Reverse Current




Figure 3. Capacitance

www.mccsemi.com



### **Ordering Information :**

Device	Packing
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel

#### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com