



BNC BULKHEAD RECEPTACLES

| Description | Terminal Type | Dimensions, inches (mm) | | | | Notes | | Mtg. Hole | Military Number | Amphenol Number | Fig. |
|--------------------------------------------------------|---------------|-------------------------|------------|------------|-----------|-------|-------|-----------|-----------------|-----------------|------|
| | | a | b | d | e | Plt. | Ins. | | | | |
| Front Mount, Isolated from Panel | Solder Cup | 1.19(30.2) | .500(12.7) | .471(12.0) | .187(4.8) | P1 | D22 | Z | — | 31-10* | ▲ |
| | Solder Cup | 1.18(30.0) | .500(12.7) | .471(12.0) | .125(3.2) | P1 | D22 | Z | — | 31-10-RFX | ▲ |
| Front Mount | Solder Cup | 1.18(30.0) | .500(12.7) | .471(12.0) | .187(4.8) | P7 | D22 | Z | — | 31-10-RFXG1 | ▲ |
| Front Mount | Solder Cup | 1.06(27.0) | .500(12.7) | .484(12.3) | .125(3.2) | P1 | D1 | U | UG-1094/U | 31-221* | ▲ |
| | | 1.06(27.0) | .500(12.7) | .472(12.0) | .125(3.2) | P7 | D23 | U | — | 31-221-RFX | ▲ |
| | | 1.06(27.0) | .500(12.7) | .469(11.9) | .156(4.0) | P1 | D1 | T | UG-625B/U | 31-236* | ▲ |
| | | 1.19(30.2) | .500(12.7) | .481(12.3) | .250(6.4) | P1 | D1 | U | UG-1094A/U | 31-2221 | ▲ |
| Front Mount, Gold Plated Contact | Solder Cup | 1.19(30.2) | .500(12.7) | .484(12.3) | .250(6.4) | P34 | D1 | U | M39012/21-0002 | 31-3376* | ▲ |
| Front Mount, Pressurized | Solder Cup | 1.30(32.9) | .578(14.7) | .594(15.1) | .250(6.4) | P1 | D9 | P | UG-657A/U | 31-239* | ▲ |
| Front Mount, Pressurized | Solder Cup | 1.30(32.9) | .578(14.7) | .594(15.1) | .250(6.4) | P1 | D9 | P | UG-657/U | 31-102* | ▲ |
| Fr. Mount, Gold Plated Contact | Spade | 1.20(30.6) | .594(15.1) | .516(13.1) | .250(6.4) | P33 | D1 | U | M39012/24-0002 | 31-4238* | ▲ |
| Hermetic External Tooth Lockwasher | Spade | 1.20(30.6) | .594(15.1) | .516(13.1) | .250(6.4) | P1 | D/11 | U | UG-912/U | 31-238* | ▲ |
| Front Mount | Solder Cup | 1.06(27.0) | .500(12.7) | .472(12.0) | .156(4.0) | P1 | D1 | T | UG-625/U | 5575* | ▲ |
| Rear Mount, Hermetic | Spade | 1.34(34.0) | .687(17.4) | .831(21.1) | .250(6.4) | P33 | D1/11 | Y | M39012/24-0001 | 31-4237* | ▲ |
| Front Mount Isolated from Panel Metal Mounting Threads | Solder Cup | 1.06(27.0) | .625(15.9) | .571(14.5) | .187(4.7) | P4 | D1 | Y | — | 31-4890-1 | ▲ |

* recognized under the component program of U.L., Inc. ▲ distributor stocked