

## Linear Systems replaces discontinued Siliconix U423

The U423 is a high input impedance Monolithic Dual N-Channel JFET

The U423 monolithic dual n-channel JFET is designed to provide very high input impedance for differential amplification and impedance matching. Among its many unique features, this series offers operating gate current specified at -250 fA. The U423 is a direct replacement for discontinued Siliconix U423.

The 6 Pin SOT-23 package provides ease of manufacturing, and a lower cost assembly option.

(See Packaging Information).

### U423 Applications:

- Ultra Low Input Current Differential Amps
- High-Speed Comparators
- Impedance Converters

### FEATURES

HIGH INPUT IMPEDANCE	$I_G = 0.25\text{pA MAX}$
HIGH GAIN	$g_{fs} = 120\mu\text{mho MIN}$
LOW POWER OPERATION	$V_{GS(OFF)} = 2\text{V MAX}$

### ABSOLUTE MAXIMUM RATINGS @ 25°C (unless otherwise noted)

#### Maximum Temperatures

Storage Temperature	-65°C to +150°C
Operating Junction Temperature	+150°C

#### Maximum Voltage and Current for Each Transistor – Note 1

$-V_{GSS}$	Gate Voltage to Drain or Source	40V
$-V_{DSO}$	Drain to Source Voltage	40V
$-I_{G(f)}$	Gate Forward Current	10mA

#### Maximum Power Dissipation

Device Dissipation @ Free Air – Total	400mW @ +125°C
---------------------------------------	----------------

### MATCHING CHARACTERISTICS @ 25°C UNLESS OTHERWISE NOTED


SYMBOL	CHARACTERISTICS	VALUE	UNITS	CONDITIONS
$ \Delta V_{GS1-2}/\Delta T _{\text{max}}$	DRIFT VS. TEMPERATURE	40	$\mu\text{V}/^\circ\text{C}$	$V_{DG}=10\text{V}$ , $I_D=30\mu\text{A}$ $T_A=-55^\circ\text{C}$ to $+125^\circ\text{C}$
$ V_{GS1-2} _{\text{max}}$	OFFSET VOLTAGE	25	mV	$V_{DG}=10\text{V}$ , $I_D=30\mu\text{A}$

### ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
$BV_{GSS}$	Breakdown Voltage	40	60	--	V	$V_{DS} = 0$ $I_G = 1\text{nA}$
$BV_{GGO}$	Gate-To-Gate Breakdown	40	--	--	V	$I_G = 1\mu\text{A}$ $I_D = 0$ $I_S = 0$
<b>TRANSCONDUCTANCE</b>						
$Y_{fss}$	Full Conduction	300	--	1500	$\mu\text{mho}$	$V_{DS} = 10\text{V}$ $V_{GS} = 0\text{V}$ $f = 1\text{kHz}$
$Y_{fs}$	Typical Operation	120	200	350	$\mu\text{mho}$	$V_{DG} = 10\text{V}$ $I_D = 30\mu\text{A}$ $f = 1\text{kHz}$
<b>DRAIN CURRENT</b>						
$I_{DSS}$	Full Conduction	60	--	1000	$\mu\text{A}$	$V_{DS} = 10\text{V}$ $V_{GS} = 0\text{V}$
<b>GATE VOLTAGE</b>						
$V_{GS(off)}$	Pinchoff voltage	--	--	2.0	V	$V_{DS} = 10\text{V}$ $I_D = 1\text{nA}$
$V_{GS}$	Operating Range	--	--	1.8	V	$V_{DG} = 10\text{V}$ $I_D = 30\mu\text{A}$
<b>GATE CURRENT</b>						
$I_{Gmax}$	Operating	--	--	.25	$\mu\text{A}$	$V_{DG} = 10\text{V}$ $I_D = 30\mu\text{A}$
$-I_{Gmax}$	High Temperature	--	--	250	$\mu\text{A}$	$T_A = +125^\circ\text{C}$
$I_{GSSmax}$	At Full Conduction	--	--	1.0	$\mu\text{A}$	$V_{DS} = 0\text{V}$ $V_{GS} = 20\text{V}$
$-I_{GSSmax}$	High Temperature	--	--	1.0	$\mu\text{A}$	$T_A = +125^\circ\text{C}$
<b>OUTPUT CONDUCTANCE</b>						
$Y_{OSS}$	Full Conduction	--	--	10	$\mu\text{mho}$	$V_{DS} = 10\text{V}$ $V_{GS} = 0\text{V}$
$Y_{OS}$	Operating	--	0.1	3.0	$\mu\text{mho}$	$V_{DG} = 10\text{V}$ $I_D = 30\mu\text{A}$
<b>COMMON MODE REJECTION</b>						
CMR	$-20 \log  \Delta V_{GS1-2}/\Delta V_{DS} $	--	90	--	dB	$\Delta V_{DS} = 10$ to $20\text{V}$ $I_D = 30\mu\text{A}$
	$-20 \log  \Delta V_{GS1-2}/\Delta V_{DS} $	--	90	--	dB	$\Delta V_{DS} = 5$ to $10\text{V}$ $I_D = 30\mu\text{A}$
<b>NOISE</b>						
NF	Figure	--	--	1	dB	$V_{DG} = 10\text{V}$ $I_D = 30\mu\text{A}$ $R_G = 10\text{M}\Omega$ $f = 10\text{Hz}$
$e_n$	Voltage	--	20	70	$\text{nV}/\sqrt{\text{Hz}}$	$V_{DG} = 10\text{V}$ $I_D = 30\mu\text{A}$ $f = 10\text{Hz}$
		--	10	--		$V_{DG} = 10\text{V}$ $I_D = 30\mu\text{A}$ $f = 1\text{KHz}$
<b>CAPACITANCE</b>						
$C_{ISS}$	Input	--	--	3.0	pF	$V_{DS} = 10\text{V}$ $V_{GS} = 0$ $f = 1\text{MHz}$
$C_{RSS}$	Reverse Transfer	--	--	1.5	pF	

### Available Packages:

LSU423 in SOT-23  
LSU423 available as bare die  
Please contact [Micross](http://www.micross.com) for full package and die dimensions  
Email: [chipcomponents@micross.com](mailto:chipcomponents@micross.com)



Micross Components Europe



Tel: +44 1603 788967

Email: [chipcomponents@micross.com](mailto:chipcomponents@micross.com)

Web: <http://www.micross.com/distribution>