



1201-14-9

REVISIONS	
ISSUE	CHANGES
0	ER JCA 33866 04/21/92
1	CN MJB 34086 E 08/19/92
2	ER RMS 8354 05/28/08
D	REVISED PER DMF304 & ER34205 KPL 08/05/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE: 4:1
 APPROX SURFACE AREA
 WAS: E-17405
 CAGE CODE: 91836
 REF: BOEING

JACK, PANEL, N

DRAWN JCA	DATE 04/21/92
DESIGN JT	DATE 04/22/92
APPR.	DATE

KINGS
 by WINCHESTER
 Winchester Electronics Corporation
 62 Barnes Industrial Road North
 Wallingford, Connecticut 06492

- NOTES:
- FOR USE WITH BOEING BMS13-65 OJ & ADAMS RUSSELL FC38Z CABLES.
 - FOR CABLING INSTRUCTIONS SEE 3-546-2.
 - FOR CRIMPING USE DIE KTH-2213.
 - INTERFACE PER MIL-STD-348, FIG. 304-2.
 - FOR USE WITH .22 MAX. PANEL.
 - CENTER CONTACT (1-534-85MA9) SUPPLIED UNASSEMBLED.
 - MARK PACKAGE: KINGS 1201-14-9 (DATE CODE)
 - MATERIALS:
 INSULATOR: TEFLON, ASTM-D1710
 K-GRIP SLEEVE: COM. BRONZE TUBE, ASTM B135
 CENTER CONTACT: BER. COP., ASTM-B196
 ALL OTHER PARTS: BRASS, ASTM-B16

- FINISHES:
 CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM-B488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
- ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 1000 VRMS
 FREQUENCY RANGE: DC TO 11 GHz
 INSERTION LOSS: DC TO 2.5 GHz, 0.035 dB MAX
 2.5 TO 5.0 GHz, 0.125 dB MAX
- WEIGHT: 39.2 GRAMS

1201-14-9