



6N80

Preliminary

Power MOSFET

6A, 800V N-CHANNEL POWER MOSFET

DESCRIPTION


The UTC **6N80** is a N-channel mode power MOSFET using UTC's advanced technology to provide customers with planar stripe and DMOS technology. This technology specialized in allowing a minimum on-state resistance and superior switching performance. It also can withstand high energy pulse in the avalanche and commutation mode.

The UTC **6N80** is universally applied in high efficiency switch mode power supply.

FEATURES

- * $R_{DS(on)} = 2.0\Omega @ V_{GS} = 10V$
- * Improved dv/dt capability
- * Fast switching
- * 100% avalanche tested

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
6N80L-TA3-T	6N80G-TA3-T	TO-220	G	D	S	Tube
6N80L-TF3-T	6N80G-TF3-T	TO-220F	G	D	S	Tube
6N80L-TF1-T	6N80G-TF1-T	TO-220F1	G	D	S	Tube

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>6N80L - TA3 - T</p> <p>(1) Packing Type (2) Package Type (3) Lead Free</p>	<p>(1) T: Tube (2) TA3: TO-220, TF3: TO-220F, TF1: TO-220F1 (3) G: Halogen Free, L: Lead Free</p>
---	---



■ ABSOLUTE MAXIMUM RATINGS ($T_C=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	800	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current (Note 1)	Continuous	I_D	6	A
	Pulsed	I_{DM}	22	A
Avalanche Energy	Single Pulsed (Note 2)	E_{AS}	680	mJ
	Repetitive (Note 1)	E_{AR}	15.8	mJ
Peak Diode Recovery dv/dt (Note 3)		dv/dt	4.5	V/ns
Power Dissipation	TO-220	P_D	138	W
	TO-220F/TO-220F1		51	W
Junction Temperature		T_J	+150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55~+150	$^\circ\text{C}$

Note: 1. Repetitive Rating: Pulse width limited by maximum junction temperature

2. $L = 37\text{mH}$, $I_{AS} = 6\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$

3. $I_{SD} \leq 5.5\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$

4. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL CHARACTERISTICS

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient		θ_{JA}	62.5	$^\circ\text{C}/\text{W}$
Junction to Case	TO-220	θ_{JC}	0.9	$^\circ\text{C}/\text{W}$
	TO-220F/TO-220F1		2.45	$^\circ\text{C}/\text{W}$







■ ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	$I_D=250\mu\text{A}$, $V_{GS}=0\text{V}$	800			V
Breakdown Voltage Temperature Coefficient		$\Delta BV_{DSS}/\Delta T_J$	Reference to 25°C , $I_D=250\mu\text{A}$		0.97		$\text{V}/^\circ\text{C}$
Drain-Source Leakage Current		I_{DSS}	$V_{DS}=800\text{V}$, $V_{GS}=0\text{V}$			10	μA
			$V_{DS}=640\text{V}$, $T_C=125^\circ\text{C}$			100	
Gate- Source Leakage Current	Forward	I_{GSS}	$V_{GS}=+30\text{V}$, $V_{DS}=0\text{V}$			100	nA
	Reverse		$V_{GS}=-30\text{V}$, $V_{DS}=0\text{V}$			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	$V_{DS}=V_{GS}$, $I_D=250\mu\text{A}$	3.0		5.0	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	$V_{GS}=10\text{V}$, $I_D=3\text{A}$		1.6	2.0	Ω
Forward Transconductance		g_{FS}	$V_{DS}=50\text{V}$, $I_D=3\text{A}$ (Note 1)		5.4		S
DYNAMIC PARAMETERS							
Input Capacitance		C_{ISS}	$V_{GS}=0\text{V}$, $V_{DS}=25\text{V}$, $f=1.0\text{MHz}$		1010	1310	pF
Output Capacitance		C_{OSS}			90	115	
Reverse Transfer Capacitance		C_{RSS}			8	11	
SWITCHING PARAMETERS							
Total Gate Charge		Q_G	$V_{GS}=10\text{V}$, $V_{DS}=640\text{V}$, $I_D=6\text{A}$ (Note 1, 2)		21	30	nC
Gate to Source Charge		Q_{GS}			6		
Gate to Drain Charge		Q_{GD}			9		
Turn-ON Delay Time		$t_{D(ON)}$	$V_{DD}=400\text{V}$, $I_D=6\text{A}$, $R_G=25\Omega$ (Note 1, 2)		26	60	ns
Rise Time		t_R			65	140	
Turn-OFF Delay Time		$t_{D(OFF)}$			47	105	
Fall-Time		t_F			44	90	
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I_S				6	A
Maximum Body-Diode Pulsed Current		I_{SM}				22	A
Drain-Source Diode Forward Voltage		V_{SD}	$I_S=6\text{A}$, $V_{GS}=0\text{V}$			1.4	V
Reverse Recovery Time		t_{rr}	$I_S=6\text{A}$, $V_{GS}=0\text{V}$,		615		ns
Reverse Recovery Charge		Q_{RR}	$dI_F/dt=100\text{A}/\mu\text{s}$ (Note 1)		5.4		



Note: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

2. Essentially independent of operating temperature

■ TEST CIRCUITS AND WAVEFORMS



■ TEST CIRCUITS AND WAVEFORMS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.