

BC2402A



Feature

1. COB with metal frame
2. 5x7 dots with cursor
3. Built-in controller KS0066 or equivalent
4. + 5V single power supply
5. 1/16 duty cycle
6. LED B/L pins: 15/16, or A/K, or 1/2
7. Option: LED array , EL B/L
8. Option: +3V single power supply
9. Option: negative voltage (built-in, external)



Mechanical Data

| Item | Standard Value | Unit |
|------------------|----------------|------|
| Module Dimension | 118.0 x 36.0 | mm |
| Viewing Area | 94.5 x 16.0 | mm |
| Dot Size | 0.6 x 0.65 | mm |
| Character Size | 3.2 x 5.55 | mm |

Pin Assignment

| Pin | Symbol | Function |
|------|--------|----------------------------|
| 1 | Vss | GND |
| 2 | Vdd | +5V(+3V option) |
| 3 | Vo | Contrast adjustment |
| 4 | RS | H/L register select signal |
| 5 | R/W | H/L read/write signal |
| 6 | E | H --> L enable signal |
| 7~14 | DB0~7 | H/L data bus line |
| 15 | A | Power supply for B/L (+) |
| 16 | K | Power supply for B/L (GND) |

Electronic Characteristics

| Item | Symbol | Condition | Typical Value | Unit |
|---------------------|--------|------------------|---------------|------|
| Input Voltage | Vdd | Vdd = +5V | 5.0 | V |
| Supply Current | Idd | Vdd = +5V | 1.2 | mA |
| LCD Driving Voltage | Vdd-Vo | 25°C | 4.2 | V |
| LED Forward Voltage | Vf | 25°C | 4.2 | V |
| LED Forward Current | If | 25°C | 190 | mA |
| EL Power Voltage | Vel | Vel=110Vac/400Hz | | V |

Dimension

